

AI SECURITY SYSTEM

DOCUMENT ID DATE PUBLISHED

US 20250131810 A1 2025-04-24

INVENTOR INFORMATION

NAME	CITY	STATE	ZIP CODE	COUNTRY
Donegan; Edward Michael	Denver	CO	N/A	US
Delmonico; William	Burnsville	MN	N/A	US
Schmitt; Joseph	Princeton	MN	N/A	US

APPLICATION NO

[19/006386](#)

DATE FILED

2024-12-31

DOMESTIC PRIORITY (CONTINUITY DATA)

parent US continuation 18508386 20231114 parent-grant-document US 12223819 child US 19006386
parent US continuation 18075905 20221206 parent-grant-document US 11875661 child US 18508386
parent US continuation 17377213 20210715 parent-grant-document US 11626002 child US 18075905

US CLASS CURRENT:

[1/1](#)

CPC CURRENT

TYPE	CPC	DATE
CPCI	G 08 B 21/18	2013-01-01
CPCI	G 08 B 29/188	2013-01-01
CPCI	G 08 B 7/06	2013-01-01
CPCI	G 08 B 7/066	2013-01-01
CPCI	G 08 B 27/005	2013-01-01
CPCI	G 08 B 29/186	2013-01-01
CPCI	G 10 L 15/22	2013-01-01
CPCA	G 08 B 21/0423	2013-01-01
CPCA	G 08 B 21/0492	2013-01-01

KWIC Hits

Abstract

Disclosed herein are techniques for event detection and response. A method can include: receiving sensor data associated with an environment, processing the sensor data using artificial intelligence (AI) to detect an event in the environment, the AI being trained to correlate the received sensor data with different types of events, generating, based on the detected event, egress guidance for a user in the environment, returning instructions for presenting the egress guidance by a sensor device, and iteratively updating the egress guidance for the user based on (i) the sensor data and (ii) user feedback that is received from the sensor device.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. application Ser. No. 18/508,386, filed Nov. 14, 2023, which is a continuation of U.S. application Ser. No. 18/075,905, filed Dec. 6, 2022 and issued on Jan. 16, 2024 as U.S. Pat. No. 11,875,661, which is a continuation of U.S. application Ser. No. 17/377,213, filed Jul. 15, 2021 and issued on Apr. 11, 2023 as U.S. Pat. No. 11,626,002. The entirety of the disclosures of the prior applications are considered part of (and are incorporated by reference in) the disclosure of this application.

TECHNICAL FIELD

[0002] This document generally describes technology for detecting security events in a building from a variety of anomalous signals and automatically determining a floor map of a building to use for advising building occupants how to exit the building during an emergency or detected security event.

BACKGROUND

[0003] Buildings and homes can be equipped with security systems that identify security events, such as theft and/or burglary. The security systems can continuously monitor the buildings and homes, and notify occupants when a security event is detected. Some security systems can send alerts to mobile devices of the occupants. Some security systems can also contact police or other law enforcement. Some security systems can also output audio signals, such as alarms, in the building that make the occupants aware that a security event has been detected and also as a means to provoke a burglar or other criminal to leave the premises without causing more damage or harm.

[0004] For some types of emergencies and security events, such as fires, occupants can be urged to create emergency escape plans. The emergency escape plans can be in written document form and can include maps of a building layout, immediate exterior grounds, and details on windows, doors, and other exits from the building. The occupants can also be urged to develop recommendations for escaping the building during emergencies, which can take into account characteristics of each occupant as well as potential pathways that can be taken to exit from each room in the building. Fire and other emergency districts recommend that occupants become familiar with their escape plans and to rehearse them frequently. However, many occupants fail to create escape plans or update existing escape plans, let alone practice the plans regularly. Occupants may not be prepared in the event that a security event or other emergency is detected in the building.

SUMMARY

[0005] This document generally describes technology for detecting and identifying security events using signals from a distributed group of sensor devices within a premises (e.g., building, home, apartment, etc.). For example, a premises can be equipped with a group of sensor devices that are designed to unobtrusively monitor for conditions in their proximate area (e.g., within a room where the sensor devices are located), such as through being embedded within a light switch, outlet cover, light fixture, and/or other preexisting devices, structures, and/or features within a premises. Such sensor devices can include a collection of sensors that are configured to detect various conditions, such as microphones to detect sound, cameras to detect visual changes, light sensors to detect changes in lighting conditions, motion sensors to detect nearby motion, temperature sensors to detect changes in temperature, accelerometers to detect movement of the devices themselves, and/or other sensors. Such sensor devices can additionally include signaling components that are capable of outputting information to people that are nearby, such as speakers, projectors, and/or lights. These signaling components can output information, such as information identifying safe pathways for emergency egress of a building.

[0006] Sensor devices can be positioned throughout a premises and can provide sensed information about the environment within the premises to a central computing device and/or system. The central computing device and/or system can combine and use the sensed information to collectively detect security related events (e.g., emergencies) within the premises (and to distinguish between security related events and non-security events). Such a central computing device and/or system can include,

for example, a device that is located within the premises and that communicates with the sensor devices (e.g., wireless communication, wired communication). The device located within the premises can process the signals locally and/or in combination with a remote computer system (e.g., cloud-based computing system). The central computing device and/or system can generate specific outputs that are appropriate for detected events and conditions within the premises, such as transmitting alerts and/or messages regarding related events to user devices associated with the premises (e.g., home automation devices, mobile devices, smart devices, etc.), causing one or more of the sensor devices to collectively output egress and/or other guidance to people within the premises, communicating with appropriate emergency personnel (e.g., fire department, police, emergency medical services), and/or other communication.

[0007] For example, in a house that includes sensor devices that are positioned in light switches and/or outlets throughout the house, when a window breaks in the house, each of the sensors devices may detect one or more signals associated with the window breaking, such as audio from the sound of the window breaking, an increase or decrease in light within a room from glass and/or other debris being scattered when the window breaks, and/or vibrations from the window breaking. This detected information (e.g., conditions, intensity, duration) can be transmitted to the centralized computing device and/or system along with timing information (e.g., timestamp for when conditions are detected). The centralized computing device and/or system can use this information along with the relative timing of the detected conditions in combination with a physical relationship of the sensor devices to each other within the premises (e.g., a map of the positioning of the sensor devices within the premises) to determine a type of event, a severity of the event, a location of the event within the premises, and/or other event-related information.

[0008] For instance, the sensor devices that are located within a room where the window broke may detect the event with a greatest decibel level, with a greatest vibration level, and as occurring the earliest in time relative to conditions detected by other sensor devices located in other rooms (e.g., since sound travels slower than light and may dissipate as it is absorbed by walls, furniture, and other items in a house, sensor devices located in other rooms may detect the window breaking later in time and with a smaller decibel level). The centralized computing device and/or system can compare the received information and, using that information, may accurately classify the location where the event occurred (e.g., triangulate the location based on relative intensity and timing of signals detected by devices), the type and/or severity of event (e.g., categorize the type and/or severity based on patterns of detected conditions across different sensor devices), and other security-related information. Having classified the event, its location, the potential danger posed (e.g., based on event type and severity), and/or other event information, an appropriate output can be generated, such as transmitting alerts to user devices associated with the premises (e.g., transmitting push notifications to user smartphones), outputting appropriate guidance to people within the premises (e.g., directing them on safe pathway out of the premises), and/or alerting authorities.

[0009] To protect user privacy, the sensor devices may be limited to and/or restricted from detecting and transmitting particular subsets of information available for sensor-based detection. For example, a microphone that is included as part of a sensor device may be restricted to detecting decibel levels at one or more frequencies (and/or groups of frequencies) instead of detecting and transmitting entire audio waveforms. Similarly, cameras and/or light sensors may be restricted to detecting intensities of and/or changes in light across one or more frequencies and/or ranges of frequencies in the electromagnetic spectrum, such as the visible spectrum, the infrared spectrum, and/or others. Such sensor devices may be configured with such restrictions so as to permit for the devices to detect and/or transmit relevant information while at the same time avoiding potential issues related to cybersecurity that, if exploited, could provide an unauthorized third party with access to private information regarding the premises. By restricting the functionality of sensors within the sensor devices (e.g., hardware-based restrictions, firmware-based restrictions), regardless of cybersecurity threats, the sensors are not able to detect and/or transmit higher-fidelity information from within the premises, while at the same time still being able to detect information with sufficient granularity to provide useful and actionable signals for making security event determinations. However, in some instances, the sensors within the sensor devices may be unrestricted.

[0010] The sensor devices may further be configured to perform some local processing of signals to detect events before transmitting event information to the centralized computer device/system. For example, instead of transmitting a stream of decibel information to a centralized computer device/system for analysis to detect security related events, the sensor devices may perform local processing of the detected audio and, once one or more conditions and/or patterns have been detected, transmit audio information to the centralized computer device/system detailing that detected security related event. Such information can include, for example, the detected audio information and/or conditions that were satisfied to warrant the transmission to the centralized computer device/system, as well as a timestamp indicating when the audio was detected. The centralized computer device/system can synchronize clocks for the sensor devices so that when events are detected by the sensor devices, timestamps can be attached to that information across a normalized timescale. Therefore, the centralized computer device/system can identify relative timing of detected events across the different sensor devices.

[0011] The disclosed technology can determine a floor map of the premises to use for advising people within the premises about how to exit during detected security events or other emergencies. The centralized computing device/system can also create escape plans, based on pre-emergency and in-emergency motion detection of people within the premises and the floor map. The centralized computing device/system can identify and guide people to essential egress routes, which can be critical if the people have not created or rehearsed escape plans in advance. For example, it can be challenging or even impossible for people to rehearse escaping a premises when a burglar breaks in. The centralized computing device/system can therefore generate escape plans in such scenarios and provide instructions to the people that help them to safely and calmly escape the premises at the time of the detected burglary.

[0012] As another example, during a fire or other emergency, strategically placed voice and/or visual guidance prompts outputted by the sensor devices, user devices, or other devices positioned throughout the premises can instruct people in each room of the premises regarding effective egress paths, based on previously automatically identified floor maps and current emergency location information. The techniques described herein can be used to detect and advise for a variety of types of emergencies and security events, including but not limited to fires, gas leakage, water leaks, thieves entering the premises, burglary, carbon dioxide detection, and other types of security related events.

[0013] The disclosed techniques can also include an augmented reality (AR) interface to provide people with information about states of the premises (e.g., real-time information) and potential security events and non-security events. The sensor devices positioned throughout the premises can, for example, recognize voices of people within the premises. The sensor devices can learn which voices are associated with which people and can learn different tones and/or inflections in the voices. At any time, the people can speak out loud in locations that are proximate to the sensor devices and ask for a current state of the premises. The people can also ask for any other types of updates in the premises (e.g., where a child is, what the child is doing, whether there's a break-in or other emergency, what a loud sound in the kitchen was, etc.). The sensor devices can then perform the techniques described herein to detect the current state of the premises. As described throughout this disclosure, the sensor devices may also continuously and passively monitor the premises to detect and determine the current state of the premises. If the sensor devices do not detect a security related event, one or more of the sensor devices can output audio (or some other form of output) to the people that tells them everything is normal within the premises. The sensor devices can also provide output (e.g., audio) that answers whatever question the people or an occupant/user may pose (such as asking a sensor device what the loud sound in the kitchen was). If the sensor devices detect a security related event, the sensor devices can output a notification of the detected event and, based on the tone or inflection in the peoples' voices, instructions or guidance to help the people safely and calmly address the detected security event (e.g., egressing the premises along one or more predetermined escape plans).

[0014] One or more embodiments described herein can include a system for providing distributed security event monitoring in a premises. The system can include a central monitoring system for detecting a security event in a premises and a plurality of sensor devices positioned throughout the

premises. The plurality of sensor devices can be configured to (i) passively detect conditions on the premises and (ii) emit signals that indicate guidance for people in the premises when the security event is detected by the central monitoring system. Each of the plurality of sensor devices can include a suite of sensors. Each of the plurality of sensor devices can be configured to passively detect, using the suite of sensors, the conditions on the premises, and transmit the detected conditions to the central monitoring system. The central monitoring system can be configured to receive the detected conditions from one or more of the plurality of sensor devices, combine the detected conditions to generate a collective of detected conditions, determine whether the collective of detected conditions exceeds expected threshold conditions for the premises beyond a threshold amount, and identify, based on determining that the collective of detected conditions exceeds the expected threshold conditions beyond the threshold amount, a security event on the premises. The central monitoring system can also classify the security event using one or more machine learning models that were trained to identify a type of the security event using training data that correlates information about conditions detected on premises with different types of security events, and generate, based on the classified security event, instructions to produce audio or visual output at the plurality of sensor devices. The output can notify the people on the premises about the security event. The central monitoring system can also transmit the instructions to one or more of the plurality of sensor devices for the one or more of the plurality of sensor devices to emit signals indicating information about the security event.

[0015] The one or more embodiments can optionally include one or more of the following features. For example, the type of the security event can include at least one of a burglary, a theft, a break-in, a fire, a gas leak, and a flood. Classifying the security event using one or more machine learning models can include determining, based on (i) the type of the security event and (ii) a magnitude in deviation of the collective of detected conditions from the expected threshold conditions, a severity level of the security event, and determining a location of the security event based on (i) a map of the premises that was generated by the central monitoring system, (ii) timestamps indicating when the conditions were detected by the plurality of sensor devices, and (iii) positioning information of each of the plurality of sensor devices on the premises. Moreover, the central monitoring system can further be configured to transmit, based on determining that the severity level of the security event exceeds a threshold reporting level, a notification about the security event to emergency response personnel.

[0016] As another example, the expected threshold conditions can be normal conditions on the premises that have been identified by the central monitoring system based on a historic spread of conditions detected by the plurality of sensor devices over a predetermined period of time.

[0017] Sometimes, the central monitoring system can also be configured to generate instructions to produce (i) audio output when the collective of detected conditions satisfy a first output threshold condition and (ii) visual output when the collective of detected conditions satisfy a second output threshold condition. The first output threshold condition can include detection of at least one of a fire, smoke, and an obstruction of visual output devices of the plurality of sensor devices. The second output threshold condition can include detection of at least one of a fire, a break-in, a burglary, and an obstruction of audio output devices of the plurality of sensor devices.

[0018] The central monitoring system can also be further configured to determine, before detection of a security event, a map of the premises, the map indicating routes within the premises, including exits out of the premises and determine, based on the map and the collective of detected conditions, one or more exit routes that can be used by people to exit the premises. The collective of detected conditions can include location information indicating one or more locations on the premises where the security event may be located, and the exit routes can avoid the one or more locations where the security event may be located. The central monitoring system can also transmit signaling instructions to one or more of the plurality of sensor devices for the one or more of the plurality of sensor devices to emit signals that indicate to the people an exit route to exit the premises.

[0019] Sometimes, the emitted signals can comprise voice commands. The voice commands can comprise at least one of instructions to guide the people to exit the premises and information about the security event. The information about the security event can include the type of the security event, a

location of the security event, and a severity level of the security event. Sometimes, the emitted signals can comprise light signals. The light signals can include directional signals that direct the people to an exit route that avoids a location of the security event.

[0020] As another example, the suite of sensors can include at least one of a light sensor, an audio sensor, a temperature sensor, a motion sensor, a user presence sensor, an image sensor, and a smoke sensor. The audio sensor can, for example, be configured to detect changes in decibels in an area proximate to a location of the audio sensor. Sometimes, the plurality of sensor devices can be integrated into at least one of outlet covers, light switches, alert systems, thermostats, and light fixtures that are installed on the premises. One of the plurality of sensor devices can sometimes be configured to operate as the central monitoring system and the other sensor devices of the plurality of sensor devices can communicate amongst each other.

[0021] As yet another example, one or more of the plurality of sensor devices can be configured to identify the security event and transmit information about the identified security event to the central monitoring system. The central monitoring system can then receive the identified security event from one or more of the plurality of sensor devices, classify the security event, generate instructions to produce output by the plurality of sensor devices about the security event, and transmit the instructions to the plurality of sensor devices.

[0022] One or more of the plurality of sensor devices can also be configured to detect audio input from a person on the premises and transmit the audio input and a respective timestamp to the central monitoring system. The audio input can include a request for information about a current state of the premises. The central monitoring system can then be configured to receive the audio input and the respective timestamp, transmit, based on the request for information in the audio input, requests to each of the plurality of sensor devices for conditions detected at a similar time as the timestamp, receive, from one or more of the plurality of sensor devices, the conditions detected at the similar time as the timestamp, identify the current state of the premises based on comparing the detected conditions to historic threshold conditions for the premises at the similar time as the timestamp, generate instructions for the one or more of the plurality of sensor devices to provide audio output to the person indicating the current state of the premises, and transmit, to the one or more of the plurality of sensor devices, the instructions to provide audio output to the person.

[0023] As yet another example, the central monitoring system can further be configured to transmit the instructions to provide output to one or more mobile devices of the people on the premises. The instructions can cause the one or more mobile devices to output at least one of audio signals, text messages, and push notifications about the security event. Moreover, each of the plurality of sensor devices further can include an audio signal generator and a visual signal generator. The visual signal generator can include a projector that projects a lighted sign on a surface, and the surface can be one or more of a wall, a floor, and a ceiling on the premises. The premises can be at least one of a building, a home, and an apartment.

[0024] One or more embodiments described herein can also include a method for providing distributed security event monitoring in a premises. The method can include receiving, by a computing system and from a plurality of sensor devices, detected conditions on a premises. The plurality of sensor devices can include a suite of sensors that passively detect the conditions on the premises, and the plurality of sensor devices can be positioned throughout the premises. The method can also include combining, by the computing system, the detected conditions to generate a collective of detected conditions, determining, by the computing system, whether the collective of detected conditions exceeds expected threshold conditions for the premises beyond a threshold amount, identifying, by the computing system and based on determining that the collective of detected conditions exceeds the expected threshold conditions beyond the threshold amount, a security event on the premises, classifying, by the computing system, the security event using one or more machine learning models that were trained to identify a type of the security event using training data that correlates information about conditions detected on premises with different types of security events, generating, by the computing system and based on the classified security event, instructions to produce audio or visual output at the plurality of sensor devices, and transmitting, by the computing system to one or more of

the plurality of sensor devices, the instructions for the one or more of the plurality of sensor devices to emit signals indicating information about the security event. The output can notify the people on the premises about the security event.

[0025] The method can optionally include one or more of the abovementioned features. As another example, the computing system can be at least one of remote from the premises, centralized at the premises, and one of the plurality of sensor devices.

[0026] The details of one or more implementations are depicted in the associated drawings and the description thereof below. Certain implementations of the disclosed techniques may provide one or more advantages. For example, emergency plans can be generated, and used in detected security events, even if people within the premises have not previously generated, reviewed, practiced, or seen emergency plans. Dynamic evacuation guidance can be provided that is based on real-time situational information about people and compromised location(s) within the premises. Real-time information about a current detected security event can be exchanged between sensor devices positioned within the premises, mobile devices or other user devices of the people on the premises, a centralized computer device/system, and devices/systems of emergency response personnel/teams. This communication can be beneficial to ensure that people within the premises are made aware of security related events as soon as they happen and respond safely and calmly. The disclosed technology can therefore provide people with appropriate guidance and notifications that help the people to reach safety, regardless of the type of security event that is detected on the premises.

[0027] Moreover, the centralized computer device/system can evaluate possible escape routes, determined from automatically generated floor maps, select recommended escape route(s), and instruct sensor devices positioned throughout the premises and/or user devices of the people within the premises to inform the people of the recommended escape route(s). As a result, when a security event is detected, the centralized computer device/system may determine how the people can reach safety and guidance to get the people quickly and calmly to safety.

[0028] As another example, the disclosed techniques provide for passively monitoring conditions in the premises to detect security related events while also preserving privacy of people on the premises. Passive monitoring can include collection of anomalous signals, such as changes in lighting, temperature, motion, and/or decibel levels and comparing those anomalous signals to normal conditions for the premises. Sudden changes in decibel levels and/or temperature levels, for example, can be indicative of a security related event. The sensor devices, therefore, may be restricted to detect particular types of signals that do not involve higher-fidelity information from within the premises but enough granularity to provide useful and actionable signals for making security event determinations. Thus, the people on the premises may not be tracked as they go about their daily lives and their privacy can be preserved.

[0029] The disclosed techniques can also provide for accurately identifying types of security events, locations of such security events, and severity of the security events. The centralized computer device/system can, for example, be trained to identify different types of security events by correlating various different signals captured during a similar timeframe and from sensor devices in different location throughout the premises. The centralized computer device/system can, for example, correlate audio signals indicating a sharp increase in sound like a glass window breaking, motion signals indicating sudden movement near a window where the audio signals were captured, and a video feed or other image data showing a body moving near the window where the audio signals were captured to determine where and when a break-in occurred on the premises. The centralized computer device/system can also be trained to determine a severity of this identified security event based on the linked signals. Using the determined information, the centralized computer device/system can also identify appropriate action(s) to take, such as notifying people on the premises, notifying emergency response personnel, and/or providing the people with guidance to safely, quickly, and calmly egress using one or more predetermined escape plans.

[0030] The disclosed techniques also provide for seamless and unobtrusive integration of sensor devices and existing features on the premises. Sensor devices described herein can be integrated into

wall outlets, lightbulbs, fans, light switches, and other features that may already exist on the premises. Existing sensor devices, such as fire alarms, smoke detectors, temperature sensors, motion sensors, and/or existing security systems can also be retrofitted in the building to communicate detected signals with installed sensor devices, user devices, mobile devices of people on the premises, and the centralized computer device/system described herein. Such seamless and unobtrusive integration can provide for performing the techniques described throughout this disclosure without interfering with normal activities of people on the premises and an aesthetic design/appeal of the premises.

[0031] Additionally, the disclosed techniques provide for robust security systems that incorporate artificial intelligence (AI) and/or augmented reality (AR). Seamless integration of sensor devices on the premises can provide more intuitive and unobtrusive detection of security related events on the premises. Such seamless integration can also make it easier for people on the premises to learn about and get updates about current activity on the premises. For example, if an occupant hears an abnormal sound, such as a crashing sound, the occupant can speak out loud by asking a sensor device located in a same room as the occupant whether everything is okay. The sensor device can ping other sensor devices on the premises for sensed conditions and can determine, based on those sensed conditions, whether a security related event has been detected. Based on this determination, the sensor device can respond to the occupant and output information (e.g., audio output) that informs the occupant about the current state of the premises. This provides a more intuitive and easier-to-use user interface for the people on the premises, especially if the people are concerned, nervous, or otherwise in a state of frenzy. The people can therefore receive updates about conditions on the premises and/or request updates on conditions on the premises without having to use additional devices such as mobile devices or mobile applications.

[0032] As yet another example, the disclosed techniques provide for local processing at sensor devices to avoid clogging network bandwidth. Since some processing, such as determining whether detected signals are indicative of a security related event, can be performed locally at a sensor device, computing resources can be better allocated and efficiently used at the centralized computer device/system. As a result, the centralized computer device/system can more quickly and efficiently utilize available computer resources and network bandwidth to perform other processing, including but not limited to detecting security related events, assessing type and/or severity of such events, generating output and guidance for people on the premises, and determining appropriate egress plans on the premises.

[0033] Other features, objects, and advantages of the technology described in this document will be apparent from the description and the drawings, and from the claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0034] FIG. 1 is a conceptual diagram of an example centralized hub for detecting and identifying a security event in a building using a variety of anomalous signals.

[0035] FIGS. 2A-C depict example system components that can be used to perform the techniques described herein.

[0036] FIG. 3 is a flowchart of a process for detecting a security event in a building.

[0037] FIGS. 4A-B is a flowchart of an example process for detecting a security event from irregular audio signals.

[0038] FIG. 5A is a conceptual diagram of an example scenario where an occupant verbally requests an update on conditions in a building from a sensor device.

[0039] FIG. 5B is a conceptual diagram of another example scenario where the occupant verbally requests an update on conditions in the building from the sensor device.

[0040] FIG. **6** depicts example features in a building that include sensor devices integrated therein.

[0041] FIG. **7** depicts example forms of output that can be generated based on a detected security event.

[0042] FIGS. **8A-B** depict exemplary systems for providing emergency or security event detection, guidance and advisement.

[0043] FIG. **9** is an example apparatus for providing emergency guidance and advisement.

[0044] FIG. **10** is another example apparatus for providing emergency guidance and advisement.

[0045] FIG. **11** is a conceptual diagram depicting a building with sensor devices positioned throughout that provide guidance and prompts to building occupants during an identified emergency.

[0046] FIG. **12** is a schematic diagram that shows an example of a computing device and a mobile computing device.

[0047] Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

[0048] This document generally describes systems and methods for detecting security events from anomalous signals and generating floor maps and guidance based on the floor maps to assist people on a premises, such as occupants in a building, how to respond to the detected security event(s). For example, the building can be equipped with a group/plurality of sensor devices that are designed to passively and unobtrusively monitor conditions in the devices' proximate areas, such as a room where a sensor device is located. The sensor devices can be embedded in existing features or fixtures in the building, such as a light switch, outlet cover, light fixture, and/or other preexisting devices, structures, and/or features. The detected conditions can be received by a centralized hub (e.g., centralized computer device/system), which can determine whether the detected conditions exceed expected threshold levels at a particular time when the conditions are detected and/or whether the detected conditions exceed normal conditions for the building that are learned over time. The centralized hub can use the detected conditions along with relative timing of the detected conditions and a physical relationship of the sensor devices to each other in the building to determine and classify a type of security event, a severity of the event, a location of the event, and/or other event related information. Other event related information can include instructions for guiding occupants of the building to safety along one or more predetermined exit routes out of the building.

[0049] Referring to the figures, FIG. **1** is a conceptual diagram of an example centralized hub **102** for detecting and identifying a security event in a building **100** using a variety of anomalous signals. A variety of different types of security events can be detected using the disclosed techniques. The security events can include, but are not limited to, break-ins, burglary, theft, natural disasters, fire, carbon monoxide, flood, gas leaks, and other types of emergencies. The centralized hub **102** can be in communication via network(s) **114** with sensor devices **108A-N** and sensors **112A-N**. The centralized hub **102**, sensor devices **108A-N**, and/or sensors **112A-N** can also be in communication via network(s) **114** with a security system for the building **100**. Communication can be wired and/or wireless (e.g., BLUETOOTH, WIFI, ETHERNET, etc.). Communication can also be through a home network.

[0050] The centralized hub **102** can be a computer system or network of computers. The centralized hub **102** can be located at the building **100**. For example, the centralized hub **102** can be one of the sensor devices **108A-N**. The centralized hub **102** can also be any other type of computing device and/or computer system that can be integrated into the building **100**. For example, the centralized hub **102** can be a computing device or other type of device with a display screen. The centralized hub **102** can be located in a central location in the building **100**, such as near a front door **110**, and can provide building occupants with information about conditions in the building **100** as well as predetermined escape plans. The building occupants can provide updated information about the occupants and/or

the building **100** to the centralized hub **102** via the display screen. This input can then be used by the centralized hub **102** to improve or otherwise modify security event detections and escape plan determinations. The centralized hub **102** can also be remote from the building **100**. For example, the centralized hub **102** can be a cloud based computing system that is configured to identify security events based on anomalous signals that are detected and received from sensor devices and sensors in different buildings.

[0051] The sensor devices **108A-N** can be configured to continuously and passively monitor conditions throughout the building **100**. The sensor devices **108A-N** can be networked with each other (e.g., via a home network) such that they can communicate with each other. For example, in a scenario where the centralized hub **102** goes down or a connection between the sensor devices **108A-N** and the centralized hub **102** goes down, the sensor devices **108A-N** can communicate with each other to determine a state of activity in the building **100** and whether a security event is detected. Each of the sensor devices **108A-N** can also operate as a centralized hub. Sometimes, each of the sensor devices **108A-N** can take turns operating as the centralized hub. Sometimes, one of the sensor devices **108A-N** can be assigned as the centralized hub. When a sensor device operates as the centralized hub, the sensor device can ping or otherwise communicate with the other sensor devices to determine when abnormal signals are detected in the building, whether a security event has or is occurring, and what guidance or instructions can be generated and provided to building occupants.

[0052] As described further below, the sensor devices **108A-N** can include a suite of sensors that passively monitor different conditions or signals in the building **100**. For example, the sensor devices **108A-N** can include audio, light, visual, temperature, smoke, and/or motion sensors. The sensors can pick up on or otherwise detect anomalous and random signals, such as changes in decibels, flashes of light, increases in temperature, strange odors, and/or sudden movements. Therefore, the sensor devices **108A-N** may not be actively monitoring building occupants as they go about with their daily activities. In other words, to protect occupant privacy, the sensor devices **108A-N** can be limited to and/or restricted to detecting intensities of and/or changes in different types of conditions in the building **100**. The sensor devices **108A-N** may transmit particular subsets of detected information so as to protect against third party exploitation of private information regarding the occupants and the building **100**. The sensor devices **108A-N** can detect and/or transmit information such as changes or deltas in decibel levels, light, motion, movement, temperature, etc.

[0053] Some sensor devices **108A-N** can include a first subset of sensors while other sensor devices **108A-N** can include a second, third, etc. subset of sensors. As an example, a first sensor device located in a room can include audio and light sensors and a second sensor device located in the same room can include image and temperature sensors. One or more other suites of sensors in the sensor devices **108A-N** positioned throughout the building **100** are possible. The sensor devices **108A-N** can also include output devices, such as audio and visual outputs (e.g., microphones, lights, speakers, projectors, etc.) so that the sensor devices **108A-N** can provide guidance and/or instructions to building occupants when a security event is detected. As described further herein, the sensor devices **108A-N** can also provide output to the building occupants that indicates a current state of the building **100**.

[0054] For example, a building occupant can speak to one of the sensor devices **108A-N** and ask for an update on the state of the building **100**. Using the techniques described herein, the sensor device and/or the centralized hub can determine the current state of the building **100**. The sensor device can generate audio output that tells the occupant what is happening in the building **100**. The sensor device can also generate output that visually represents the current state of the building **100**. For example, using augmented reality (AR), the sensor device can project visual representations of the building **100** on a surface proximate to the occupant (e.g., on a wall and/or a floor) that indicate the current state of the building **100**. Visual representations can include an image or video clip of a particular area in the building **100** where activity was detected, text describing or explaining what activity (or inactivity) was detected in the building **100**, and the like.

[0055] The sensor devices **108A-N** can be unobtrusively integrated into the building **100**. Sometimes, the sensor devices **108A-N** can be integrated or retrofitted into existing features in the building **100**,

such as in light fixtures, light bulbs, light switches, power outlets, and/or outlet covers. The sensor devices **108A-N** can also be standalone devices that can be installed in various locations throughout the building **100** so as to not interfere with the daily activities of the building occupants and to be relatively hidden from sight to preserve aesthetic appeal in the building **100**. For example, the sensor devices **108A-N** can be installed in corners, along ceilings, against walls, etc.

[0056] In the example building **100**, the sensor devices **108A-N** are positioned in each room **106A-C**. Sensor devices **108B** and **108N** have been positioned in room **106A**. Sensor devices **108A** and **108D** have been positioned in room **106B**. Sensor device **108C** has been positioned in room **106C**. Multiple sensor devices can be positioned in one room. Sometimes, only one sensor device can be positioned in a room. Moreover, sometimes a sensor device may not be positioned in a room. Instead, the room can include one or more standalone sensors **112A-N**.

[0057] The sensors **112A-N** can be positioned throughout the building **100**. Sometimes, the sensors **112A-N** can already be installed in the building **100** before the sensor devices **108A-N** and the centralized hub **102** are added to the building **100**. For example, the sensors **112A-N** can include existing security cameras, smoke detectors, fire alarms, user motion sensors, light sensors, etc. Some of the rooms **106A-C** in the building **100** can include the sensors **112A-N** while other rooms may not. In some implementations, one or more of the sensors **112A-N** can be integrated into or otherwise part of the sensor devices **108A-N**. In the example building **100**, sensor **112A** is positioned in the room **106C** and sensor **112N** is positioned in the room **106A**. One or more additional sensors **112A-N** can be installed throughout the building **100**.

[0058] Still referring to FIG. 1, the centralized hub **102** can synchronize clocks of the sensor devices **108A-N** and optionally the sensors **112A-N**. Synchronization can occur at predetermined times, such as once a day, once every couple hours, at night, and/or during inactive times in the building. To synchronize clocks, the centralized hub **102** can send a signal with a timestamp of an event to all of the sensor devices **108A-N** and optionally the sensors **112A-N**. All the sensor devices **108A-N** can then synchronize their clocks to the timestamp such that they are on a same schedule. The centralized hub **102** can also transmit a signal to the sensor devices **108A-N** and optionally the sensors **112A-N** that indicates a local clock time. The sensor devices **108A-N** can then set their clocks to the same local time. Synchronization makes matching up or linking of detected signals easier and more accurate to detect security events in the building **100**. In other words, when security events are detected by the sensor devices **108A-N** and/or the centralized hub **102**, timestamps can be attached to detected conditions/information across a normalized scale. The centralized hub **102** and/or the sensor devices **108A-N** can accordingly identify relative timing of detected events across the different sensor devices **108A-N**, regardless of where the devices **108A-N** are located in the building **100**.

[0059] At time=1, each of the sensor devices **108A-N** and the sensors **112A-N** can passively monitor conditions in the building **100** (step A). For example, the sensor devices **108A-N** can collect temperature readings in each of the rooms **106A-C** during one or more times (e.g., every 2 minutes, every 5 minutes, every 10 minutes, etc.). As another example, the sensor devices **108A-N** can collect decibel readings in each of the rooms **106A-C** at predetermined times and/or continuously. The sensor devices **108A-N** can collect one or more other signal readings as described herein (e.g., motion, light, etc.).

[0060] As mentioned throughout, the sensor devices **108A-N** can passively monitor conditions in such a way that protects occupant privacy. The sensor devices **108A-N** may be limited to and/or restricted from detecting and transmitting particular subsets of information available for sensor-based detection. For example, an audio sensor can be restricted to detect only decibel levels at one or more frequencies (and/or groups of frequencies) instead of detecting and transmitting entire audio waveforms. Similarly, cameras, image sensors, and/or light sensors may be restricted to detecting intensities of and/or changes in light across one or more frequencies and/or ranges of frequencies in the electromagnetic spectrum, such as the visible spectrum, the infrared spectrum, and/or others. Configuring the sensor devices **108A-N** with such restrictions allows for the devices **108A-N** to detect and/or transmit relevant information while at the same time avoiding potential issues related to cybersecurity that, if exploited, could provide an unauthorized third party with access to private

information regarding building occupants. Although functionality of sensors within the sensor devices **108A-N** may be restricted, the sensor devices **108A-N** can still detect information with sufficient granularity to provide useful and actionable signals for making security event determinations and further classifications.

[0061] One or more of the sensor devices **108A-N** can detect an event at time=1 (step B). In the example of FIG. 1, the sensor device **108A** detects an event in the room **106B**. The event can be a break-in, which is represented by a brick **104** being thrown through the door **110** and into the room **106B**. The sensor device **108A** can detect the event in a variety of ways. For example, at time=1, the sensor device **108A** is passively monitoring signals (step A) in the room **106B**, at which point a sharp increase in decibel readings can be detected. The sharp increase in decibel readings can indicate the brick **104** being thrown through the door **110** and breaking glass of the door **110**. The sharp increase in decibel readings may not be a normal condition or expected signal for the building **100** or the particular room **106B**. Thus, the sensor device **108A** can detect that some abnormal event has occurred at time=1 (step B).

[0062] Likewise, the sensor device **108A** can detect a sudden movement by the door **110**, which can represent the brick **104** hitting the door **110** and landing inside of the room **106B**. The sudden detected movement may not be a normal condition or expected signal for the building **100**, the particular room **106B**, and/or at time=1. Thus, the sensor device **108A** can detect that some abnormal event has occurred at time=1 (step B).

[0063] The sensor device **108A** can transmit the detected signal(s) at time=1 to the centralized hub **102** (step C). Moreover, once an event is detected (step B), each of the sensor devices **108A-N** and optionally the sensors **112A-N** can transmit any signals that were detected at time=1 to the centralized hub **102**. This is why synchronization of clocks of the sensor devices **108A-N** and optionally the sensors **112A-N** is performed. The other sensor devices **108B-N** and the sensors **112A-N** can be notified or pinged by the sensor device **108A** when the event is detected (step B) so that the other sensor devices **108B-N** and the sensors **112A-N** can transmit signals that they detected at the same time as the event (step C). The detected signal(s) can be transmitted to the centralized hub **102** with timing information, such as a timestamp of when the signals and/or condition were detected.

[0064] Sometimes, the sensor devices **108A-N** and the sensors **112A-N** can continuously transmit detected signals (step C) to the centralized hub **102**. Therefore, the centralized hub **102** can receive a string of signals from one or more or all of the sensor devices **108A-N** and the sensors **112A-N**. The sensor devices **108A-N** and the sensors **112A-N** can transmit detected signals to the centralized hub **102** at predetermined times (e.g., every 1 minute, 2 minutes, 5 minutes, etc.). Sometimes, the sensor devices **108A-N** and the sensors **112A-N** can transmit detected signals based on receiving a request from the centralized hub **102** for the signals. For example, the centralized hub **102** can ping the sensor devices **108A-N** and the sensors **112A-N** at predetermined times and request the sensor devices **108A-N** and the sensors **112A-N** for any changes in detected signals. If changes have been detected, then the signals can be transmitted to the centralized hub **102**. If changes have not been detected then the signals may not be transmitted to the centralized hub **102**. Moreover, as described above, the sensor devices **108A-N** and the sensors **112A-N** can be triggered to transmit signals to the centralized hub only upon detection of some event by one or more of the sensor devices **108A-N** and/or the sensors **112A-N** (step B).

[0065] Once the centralized hub **102** receives the detected signals, the centralized hub **102** can determine whether any of the signals exceed expected threshold values (step D). The centralized hub **102** can combine the detected signals into a collective of signals and determine whether the collective of signals exceeds expected threshold values for the building **100**. The centralized hub **102** can also use the relative timing information and physical relationship of the sensor devices **108A-N** in the building **100** to determine, for the signals or collective of detected signals that exceed the expected threshold values, a type of security event, a severity of the event, a location of the event, and/or other event-related information.

[0066] For example, as described further below, the centralized hub **102** can compare the detected signals to historic signals that correspond to the building **100** and/or the room in which the signal was detected. For the sharp increase in decibel readings in the room **106B**, the centralized hub **102** can compare this increase to expected decibel readings for the room **106B**. The expected decibel readings for the room **106B** can be based on previous decibel readings for the room at the same or similar time as time=1. For example, if time=1 is at 8:30 in the morning, the expected decibel readings can be a historic spread of decibel readings that were taken at 8:30 in the morning over a certain number of days. At 8:30 in the morning, historic changes in decibel readings can be very low because building occupants may still be asleep at that time. Therefore, if the detected signals at time=1 is a sudden increase in decibel readings that deviates from the expected signals at time=1, the centralized hub **102** can determine that the detected signal likely represents some type of security event.

[0067] The centralized hub **102** can also determine whether any of the other received signals from the sensor devices **108A-N** and the sensors **112A-N** deviate from expected threshold values (step D). For example, the sensor device **108N** in the room **106A** at a back of the building **100** can detect a change in decibel readings that, although may be less of a sharp increase than the change in decibel readings detected by the sensor device **108A**, is abnormal for that room **106A** and/or time. After all, sound can travel slower and can bounce off of objects or other features in the building **100**, thereby causing the decibel readings in a different area of the building **100** to be of lesser magnitude. Since the clocks of the sensor devices **108A-N** are synchronized and the sensor device **108N** detected a change in decibel readings at the same or similar time that the sensor device **108A** detected a change in decibel readings, the centralized hub **102** can confirm that a security event was detected by the sensor device **108A**.

[0068] Accordingly, the centralized hub **102** can correlate the detected signals (step E). Correlating the signals can include linking signals that deviate from the expected threshold values to piece together and identify the security event. As described herein, the centralized hub **102** can correlate different types of signals to piece together the security event. For example, the centralized hub **102** can link together decibel signals from the sensor device **108A** with motion signals from the sensor device **108D** and decibel signals from one or more of the other sensor devices **108B**, **108C**, and **108N** and/or the sensors **112A** and **112N**. The centralized hub **102** can also link together the above mentioned signals with video or other image data that is captured by an existing security system inside or outside the building **100**. By correlating different types of detected signals, the centralized hub **102** can more accurately determine what type of security event has occurred at time=1.

[0069] The centralized hub **102** can identify the security event and location of the security event (step F). For example, the centralized hub **102** can use one or more machine learning models that are trained to identify a type of security event from different types of signals, correlated signals, changes/deviations in signals, etc. The centralized hub **102** can categorize the type of the security event based on patterns of detected signals across different sensor devices **108A-N** and/or sensors **112A-N**. The models can be trained using deep learning (DL) neural networks, convolutional neural networks (CNNs), and/or one or more other types of machine learning techniques, methods, and/or algorithms. The models can also be trained using training data that includes signals that have been detected by the sensor devices **108A-N** and/or the sensors **112A-N** in the building **100**. The models can be trained to identify security events based on detected signals and expected conditions of the particular building **100**. The models can also be trained to identify security events based on signals and expected conditions in a variety of different buildings.

[0070] The centralized hub **102** can determine a location of the security event (step F) based on where, for example, a deviation in detected signals is greatest. The centralized hub **102** can also determine the location based on video or other image data that can be received from one or more of the sensor devices **108A-N**, the sensors **112A-N**, and/or camera security systems installed at the building **100**. The video or other image data can capture the detected security event at time=1. In some implementations, the centralized hub **102** can determine the location by triangulating the location based on relative intensity and timing of signals that are detected by the sensor devices **108A-N** and/or the sensors **112A-N**.

[0071] As described further below, the centralized hub **102** can also determine a severity of the security event (step F). This determination can be made using one or more machine learning models. This determination can also be made based on comparing and correlating patterns of detected signals across the different sensor devices **108A-N** and/or the sensors **112A-N**.

[0072] Based on the identification of the security event, the location of the security event, and the severity of the security event, the centralized hub **102** can output an indication of the security event (step G). In some implementations, the centralized hub **102** can generate instructions that can be used by the sensor devices **108A-N** and/or one or more other devices in the building **100** to output information about the security event to building occupants.

[0073] As described further below, the centralized hub **102** can determine that building occupants should receive guidance to safely, calmly, and quickly exit the building **100**. The centralized hub **102** can determine that this guidance should be outputted as text messages to the occupant's mobile devices instead of audio or visual outputs by the sensor devices **108A-N** and/or the occupant's mobile devices. The centralized hub **102** can determine that audio or visual outputs may increase safety risks to the occupants since it can bring more attention to them. The centralized hub **102** can also automatically contact emergency response personnel to report the break-in. Determining whether to contact emergency response personnel can be based on the type of security event and the severity of the security event. When the centralized hub **102** provides guidance to help the occupants safely egress from the building **100**, the centralized hub **102** can determine optimal egress pathways based on a floorplan of the building **100**, locations of the occupants in the building, and/or the location of the security event, as described further below.

[0074] Although FIG. **1** is described in reference to an example break-in security event, the techniques described in FIG. **1** are not so limiting and apply to various types of security events and other emergencies. For example, steps A-G can be performed when fires, floods, gas leaks, and natural disasters are detected. Steps A-G can also be performed when other types of security-related events are detected in the building **100**. The techniques described herein therefore provide a robust security and emergency detection and guidance system.

[0075] Moreover, in some implementations, one or more of the steps A-G can be performed by one or more of the sensor devices **108A-N** instead of at the centralized hub **102**. For example, instead of transmitting a stream of decibel information or other detected signals to the centralized hub **102** for analysis to detect security related events, the sensor devices **108A-N** may perform local processing of the detected signals and identify patterns amongst the detected signals (such as in steps D and E). The sensor devices **108A-N** can sometimes identify a security event and information about the security event (such as in step F), and then transmit such information to the centralized hub **102**. The centralized hub **102** can perform additional processing, such as classifying the security event based on type, location, and/or severity (such as in step F). The centralized hub **102** can also determine what type of output should be generated and transmitted back to the sensor devices **108A-N** or other devices in the building **100** (such as in step G).

[0076] FIGS. **2A-C** depict example system components that can be used to perform the techniques described herein. Referring to FIG. **2A**, as described in reference to FIG. **1**, the centralized hub **102**, sensor devices **108A-N**, and sensors **112A-N** can communicate via the network(s) **114**. The centralized hub **102**, sensor devices **108A-N**, and sensors **112A-N** can also communicate with a security system **200** and building information data store **204** via the network(s) **114**.

[0077] The sensor devices **108A-N** can be configured to passively monitor anomalous signals and other conditions in a building, as described throughout this disclosure. To do so, the sensor devices **108A-N** can include a suite of sensors and other components, including but not limited to processor(s) **214**, light sensor **216**, sound sensor **218**, temperature sensor **220**, motion sensor **222**, image sensor **224**, output device(s) **226**, communication interface **228**, and power source **229**. The processor(s) **214** can be configured to perform one or more techniques and operations described herein. For example, sometimes, one or more of the sensor devices **108A-N** can be configured to operate like the centralized hub **102**. In other words, the one or more sensor devices **108A-N** can request and/or

receive detected signals from other sensor devices **108A-N** can determine whether any of the detected signals exceed expected threshold values.

[0078] The one or more sensor devices **108A-N** can then identify a security event in the building. The sensors **216**, **218**, **220**, **222**, and **224** of the sensor devices **108A-N** are further described in reference to FIG. 8A. As mentioned throughout, some sensor devices **108A-N** can include some of the sensors **216**, **218**, **220**, **222**, and **224** but not all. Moreover, some sensor devices **108A-N** can include some of the sensors **216**, **218**, **220**, **222**, and **224** while other sensor devices **108A-N** include different sensors **216**, **218**, **220**, **222**, and **224**. For example, one of the sensor devices **108A-N** positioned at a front entrance to a building can include the light sensor **216**, the sound sensor **218**, the motion sensor **222**, and the image sensor **224**. Another sensor device **108A-N** positioned in a kitchen of the building can include the light sensor **216**, the temperature sensor **220**, and the image sensor **224**, while another sensor device **108A-N** positioned in a bedroom of the building may include only the light sensor **216** and the temperature sensor **220**. A variety of other configurations of sensors in each of the sensor devices **108A-N** can be realized and installed in a building.

[0079] The output device(s) **226** of the sensor devices **108A-N** can include audio output **230** and visual output **232**. As described further below (e.g., refer to FIG. 8A), the sensor devices **108A-N** or the centralized hub **102** can determine a preferred form of outputting notifications, guidance, or other information to building occupants. Audio output can be preferred in emergency situations where, for example, there is a fire and occupants are unable to see visual guidance prompts through smoke and flames. Visual output can be preferred in some security event situations where, for example, there is a break-in and audio signals could attract a thief to a location of the building occupant(s), thereby putting the building occupant(s) at more risk.

[0080] Sometimes, the audio output **230** can also act as an input device. For example, a building occupant can speak to the sensor devices **108A-N** and ask what is happening in the building (e.g., refer to FIGS. 5A-B). The audio output **230** can detect the occupant's voice and, based on the request from the occupant, ping the other sensor devices **108A-N** to collect detected signals and determine whether any security event has occurred in the building. The audio output **230** can then output information to the occupant about the current state of the building. The visual output **232** can also output information about the current state of the building. For example, the visual output **232** can project text or other visualizations depicting the current state of the building on one or more surfaces proximate the building occupant. Images captured of a room in the building can, for example, be projected on a wall near the occupant. Video captured of a room in the building can also be projected on the wall such that the occupant can watch, in real-time, what is happening in the building. This feature therefore provides for AR interaction between the building occupants, the sensor devices **108A-N**, and the centralized hub **102** such that the building occupants can easily and intuitively remain up to date about what is currently happening in the building. As a result, building occupants can feel more comfortable and safe in the building since they can always talk to the sensor devices **108A-N** and receive, as feedback, guidance about what the occupants can do to feel more comfortable and/or safe in the building.

[0081] The communication interface **228** can be configured to provide communication between the sensor devices **108A-N** and the components described throughout. The sensor devices **108A-N** can also include the power source **229**, which can provide power to the sensor devices **108A-N**. The power source **229** can be any type of power supply, including but not limited to batteries, solar energy, and/or plug-in battery packs. Sometimes, the sensor devices **108A-N** may not have the power source **229**. Sometimes, the power source **229** can be rechargeable. Moreover, in the event that an external power source powering the sensor devices **108A-N** goes down, a local power source, such as the power source **229**, can be automatically activated to power the sensor devices **108A-N**. As a result, the sensor devices **108A-N** can continue to operate and function normally with the local power source **229**. In such scenarios, the power source **229** can act as a backup power supply.

[0082] As mentioned herein, the centralized hub **102**, the sensor devices **108A-N**, and the sensors **112A-N** can communicate with the security system **200**. The security system **200** can be a separate system that is already installed in the building and/or installed at a same or later time as the

centralized hub **102**. The security system **200** can provide for known safety and security monitoring. Integration of the security system **200** with the disclosed techniques can provide for improved and more effective security monitoring in the building. The security system **200** can include, for example, additional sensors, cameras, or other devices that continuously monitor different areas inside and/or surrounding the building. Data collected by the security system **200** can be used by the centralized hub **102** in order to more accurately detect security events, identify types of security events, and determine severity levels of the security events. The security system **200** can also include information about known types of security events and signals or conditions in the building that can be indicative of different types of security events. The centralized hub **102** can use this information to more accurately determine what type of security event has been detected in the building.

[0083] The centralized hub **102**, as described throughout this disclosure, can detect security events, notify relevant parties about the detected security events, determine floor maps and escape plans for building occupants, and generate egress guidance or instructions for building occupants when security events or emergencies are detected. Accordingly, the centralized hub **102** can include an emergency egress module **206**, a security module **208**, and a communication interface **234**. The communication interface **234** can provide communication between the centralized hub **102** and one or more of the components described herein.

[0084] The emergency egress module **206** of the centralized hub **102** can be configured to determine floor maps of the building, escape plans, and guidance to assist building occupants in safely and calmly egressing during an emergency or security event. In reference to FIG. **2B**, the emergency egress module **206** can include a building layout determiner **236**, an emergency identification module **238**, an emergency guidance determiner **240**, and an output generator **242**.

[0085] The emergency egress module **206** is described further in reference to FIG. **2C**. Briefly, the building layout determiner **236** is configured to generate floor maps of the building. These floor maps can be saved as building layouts **210A-N** in the building information data store **204** (e.g., refer to FIG. **2A**). The building layout determiner **236** can also predict different emergency scenarios using the generated floor maps and determine safe ways for occupants to escape the building in the predicted emergency scenarios. Prediction of emergency scenarios can be performed with artificial intelligence (AI) techniques, processes, and/or algorithms, predictive analytics, and/or one or more machine learning models. Thus, the building layout determiner **236** can generate egress or escape plans for the building based on the building floor maps and/or additional information, such as information or characteristics about building occupants (e.g., age, agility level, disabilities, etc.) that can be received from the security system **200** and/or the user devices **252A-N**. Generated egress plans can also be stored in the building information data store **204**.

[0086] During runtime, the emergency identification module **238** can be configured to identify when an emergency occurs in the building. The emergency identification module **238** can, for example, communicate with the sensor devices **108A-N** and the sensors **112A-N** to receive real-time readings of conditions in the building. Based on these readings, the emergency identification module **238** can determine when and if an emergency, such as a fire, gas leak, etc., occurs. Sometimes, the security module **208** can identify a variety of security events that can include emergencies. When the security module **208** detects an emergency, the security module **208** can transmit a notification indicating the detected emergency to the emergency identification module **238**. Sometimes, when the security module **208** detects a security event, such as a break-in, the security module **208** can notify the emergency egress module **206** such that the emergency egress module **206** can provide appropriate guidance to help the building occupants escape the building.

[0087] The emergency guidance determiner **240** can generate escape plans before an emergency occurs in the building. The emergency guidance determiner **240** can also select predetermined escape plans during runtime, when an emergency is detected. The emergency guidance determiner **240** can select escape plans based on current locations of building occupants relative to a location of the emergency and information about the building occupants, such as their age, agility level, disability, etc.

[0088] The output generator **242** can be configured to select an optimal form of outputting guidance to the building occupants during an emergency. This selection can be made based on current conditions in the building. For example, if there is a fire and a building occupant is detected to be in a room with a significant amount of smoke, the output generator **242** can select audio guidance as the preferred form of output for this particular building occupant. As another example, if the building occupant is deaf, then the output generator **242** can select visual guidance, such as strobe lights, flashing lights, or other signals that help direct the building occupant to safety. The output generator **242** can also determine whether to provide the output at the sensor devices **108A-N** and/or the user devices **252A-N**. Such a determination can be made based on building occupant's preselected preferences and/or locations of the building occupants relative to the emergency and/or the sensor devices **108A-N**.

[0089] Still referring to the emergency egress module **206**, FIG. 2C is a conceptual diagram depicting the emergency egress module **206** in operation, when it automatically determines a floor map of the building and uses the floor map for advising occupants how to exit the building during a detected emergency. The emergency egress module **206** can monitor the building (e.g., a home) and can communicate with various devices within the building using one or more wired and/or wireless network(s) **114**. For example, the emergency egress module **206** can communicate with a set of user detection devices **202A-N** that can detect a presence and movement of occupants within the building, at particular locations within the building. The user detection devices **202A-N** can provide user presence information **264** to the emergency egress module **206**. The user detection devices **202A-N** can be of various configurations, such as motion sensors, cameras, door sensors, window sensors, door locks and window locks, other security devices, or sensors **112A-N**, etc.

[0090] The building layout determiner **236** included in the emergency egress module **206** can use the user presence information **264** to determine and store a floor map **262** of the building (e.g., the building layout **210A-N** in the building information data store **204** depicted in FIG. 2A). The floor map **262** indicates routes within the building, including exits out of the building.

[0091] One or more emergency detection devices **112A-N** (e.g., the sensors **112A-N**) can also be located within the building to detect different types of emergencies, such as fires and/or gas leaks. The emergency detection devices **112A-N** can be of various configurations, such as a smoke detector and a heat sensor (e.g., a temperature sensor, an infrared sensor, etc.).

[0092] The emergency egress module **206** can receive emergency indication information **266** from the emergency detection devices **112A-N** that may indicate one or more locations within the building that may have an emergency. The emergency identification determiner **238** in the emergency egress module **206** can determine whether the emergency indication information **266** indicates the presence of an emergency in the building. The emergency indication information **266** can be temperature readings for example.

[0093] The building layout determiner **236** can determine, in response to the emergency identification module **238** determining presence of the emergency, one or more exit routes **260** that can be used by occupants to exit the building, based on the floor map **262** and the emergency indication information **266**. Sometimes, as described in reference to FIG. 2B, the emergency guidance determiner **240** can determine the one or more exit routes **260**. The determined exit routes **260** can be selected so as to avoid the locations within the building that may have the emergency (e.g., the emergency indication information **266** can indicate location(s) of single or multiple emergencies within the building).

[0094] The output generator **242** can generate and send signaling instructions **268** to the sensor devices **108A-N** located in the building, for the sensor devices **108A-N** to emit signal(s) to indicate to occupants the determined routes **260** out of the building. The emitted signals can be voice commands, lighted signals, or other signals, as described in more detail below.

[0095] The emergency egress module **206** can further include a system improvement engine **256**. The improvement engine **256** can employ machine learning to improve various functions of the emergency egress module **206**, such as functions performed by the building layout determiner **236**, the emergency identification determiner **238**, and the output generator **242**. In some embodiments, the

improvement engine **256** is configured to include one or more engines that are separate from the other modules or engines (e.g., the building layout determiner **236**, the emergency identification determiner **238**, and the output generator **242**) in the emergency egress module **206**. Alternatively, the modules or engines of the emergency egress module **206** can be configured to operate or otherwise perform functions of the improvement engine **256**.

[0096] In some examples, the improvement engine **256** is configured to process an input, such as the user presence information **264**, and generate a floor map **262** based on the input. In addition or alternatively, the improvement engine **256** is configured to process an input, such as the floor map **262** and the emergency indication information **266**, and generate, based on the input, one or more exit routes **260** which are used to evacuate occupants in the building.

[0097] In some examples, the improvement engine **256** can be trained to generate and update the floor map **262** adapted to changing aspects of occupancy by residents as well as visitors of a building. Further, the improvement engine **256** can be trained to predict presence and whereabouts of occupants in a building in response to determination of presence of an emergency and generate at least one exit route **260**.

[0098] The improvement engine **256** operates to bolster functioning and effectiveness of the emergency egress module **206** by adjusting the module **206** for changing circumstances in occupant status or occasions with guests. As such, an egress plan for a building can be modified rapidly with changing occupant circumstances including guest visitation. Such a plan can be stored locally in the module **206** and in a cloud for redundancy. In certain examples, biometric sensing devices are also employed in implementing the improvement engine **256** and/or other operations of the module **206**.

[0099] In addition to real-time exit route guidance, a general building escape plan can be automatically created, based on automatically-determined floor maps, and made available for occupants, to view and rehearse, before emergencies occur. Generated plans can be stored both locally in the emergency egress module **206**, as well as in the cloud for failsafe redundancy. Generated plans can be viewed and maintained by occupants. For example, occupants can update a plan, such as when changes in occupancy occur over time, or when changes in family membership occur (e.g., newborns, grown children leaving the household, deaths, and so forth), and occasions with babysitters or house guests in the home.

[0100] Although the emergency egress module **206** is described in reference to emergencies such as fires and/or gas leaks, the emergency egress module **206** can perform similar or same functions when the security module **208** detects a security event, such as a break-in, theft, and/or burglary. Accordingly, the emergency egress module **206** can determine appropriate and safe escape plans for building occupants during the detected security event.

[0101] Referring back to FIG. **2B**, the security module **208** can be configured to detect security events in the building during runtime and to generate output that can notify building occupants or other relevant stakeholders of the detected security events. The security module **208** can include a normal conditions determiner **244**, a voice learning module **246**, a security event detector **248**, and an output generator **250**.

[0102] The normal conditions determiner **244** can be configured to learn different states or conditions of the building. The normal conditions determiner **244** can use one or more machine learning trained models to identify and determine normal values for signals that are detected throughout the building. The normal conditions determiner **244** can receive detected signals from the sensor devices **108A-N** over certain periods of time. For example, the determiner **244** can collect signals over several 24 hour windows of time in order to identify what sounds, lights, motion, and/or visuals are typical during a normal day in the building. The determiner **244** can also collect signals during particular time periods, such as from 8 am to 10 am every morning for 5 consecutive days.

[0103] The received signals can be fed into one or more machine learning models as input. Output from the models can be indications and/or ranges of expected values for different signals that may be

detected in the building. Sometimes, the output from the models can also indicate or otherwise classify the signals that may normally be detected in the building. For example, if audio signals are barely detected between the hours of 11 am and 8 am on most days, the normal conditions determiner **244** can determine that the building occupants likely start waking up and getting ready for the day after 8 am. As another example, if visual signals from a camera near a front door of the building shows children leaving the house at 8:30 am on most days and returning around 4:30 pm, then the normal conditions determiner **244** can determine that the building occupants are likely gone from the building during that 8 hour window of time. Therefore, any anomalous signals detected during that 8 hour window of time on most days may be indicative of a security event. As yet another example, if temperature signals positioned in a kitchen of the building indicate increased temperature readings around 7 pm at night on most days, then the normal conditions determiner **244** can determine that the building occupants likely cook their dinners during that time most evenings. Therefore, abnormal increases in temperature during other periods of time during the day can be indicative of some security event and/or emergency.

[0104] The normal conditions determiner **244** can also use one or more machine learning models to continuously learn and modify the normal conditions of the building. The normal conditions of the building can be updated to reflect temporary changes and also long term changes. For example, there can be days where guests are invited in the building and detected signals are abnormally high relative to a historic spread of detected signals during similar or same periods of time. The normal conditions determiner **244** can receive detected signals from a variety of sensor devices **108A-N** and correlate those signals in order to determine that the abnormally high signals are due to a dinner party rather than a security event. The machine learning models can be trained to classify and/or correlate different types of signals with different categories of activities that constitute normal conditions for a building. For example, during a dinner party, audio signals can be much higher than typical audio signals. The audio signals during the dinner party can also continue over a long period of time, such as several hours. A security event, such as a break-in, can have higher audio signals than the typical audio signals, however such audio signals would occur briefly over a short period of time, such as several seconds and/or minutes. The machine learning models can be trained to identify magnitude and duration of changes in detected signals, such as the audio signals described above, and classify the detected signals based on the identified magnitude and duration of change. In the example of the dinner party, since the detected audio signals are consistently high for several hours, the machine learning models can identify that the detected audio signals are associated with activity that does not constitute a security threat.

[0105] Sometimes, the normal conditions determiner **244** can also receive input from building occupants about changes to the building. This input can be fed into the machine learning models in order to improve or otherwise update the normal conditions for the building. The input can indicate temporary changes to a current state of the building. Examples include overnight guests, the building occupants going on vacation for a certain amount of time, a babysitter spending a couple hours there, the building occupants leaving for a day-long excursion/activity, a party, etc. The input can also indicate more long term changes to the current state of the building. Examples include a dog or other pet becoming part of the building household, a newborn child, an occupant dying, a child beginning to play and practice an instrument, a weekly meetup in the building with guests from outside the building household, a particular window of time every week when all the building occupants are away from the building, etc.

[0106] The input can be received from mobile devices of the building occupants, such as the user devices **252A-N**. For example, the building occupants can provide updates to the normal conditions of the building via a user interface in a mobile application. The mobile application can communicate with the centralized hub **102** and/or the sensor devices **108A-N** to provide the building occupants with information about current conditions in the building. The input can also be provided by the occupants directly to the centralized hub **102** and/or the sensor devices **108A-N**. For example, a building occupant can speak to the sensor device **108A**. The occupant can tell the sensor device **108A** that changes have been made to the building. The sensor device **108A** can relay (e.g., transmit) the occupant's verbal message to the security module **208** of the centralized hub **102**, where the verbal message can be dissected (e.g., by the voice learning module **246**) and used to update normal

conditions for the building (e.g., by the normal conditions determiner **244**). The centralized hub **102** and/or the sensor devices **108A-N** can also include a user interface presented via input and output devices such as a touchscreen display where the occupants can not only view information about the current conditions in the building but also provide information to update the normal conditions in the building.

[0107] In determining the normal conditions of the building, the normal conditions determiner **244** can average the signals in order to determine a baseline or threshold value for the signals. The baseline or threshold value for the signals can indicate normal conditions for the building during the designated time period. The normal conditions determiner **244** can also find a median and/or mean value for the signals from a designated time period in order to identify the normal conditions for the building. Therefore, the normal conditions determiner **244** can take a historic spread of detected signals in order to determine what is normal for the building.

[0108] Learning the normal conditions for the building can be advantageous to use as a baseline in determining whether detected anomalous signals are out of the ordinary and indicative of a security event. For example, if a loud crashing sound is detected at 8 am in the morning and the historic spread of sound signals indicates that minimal noise is detected between 5 am and 9 am, then the security module **208** can determine that the loud crashing sound is likely a security event. Correlating various signals that are detected at a same time as the loud crashing sound can be performed by the security module **208** in order to confirm that a security event in fact occurred and that the loud crashing sound wasn't some random activity, such as a book falling off a shelf.

[0109] Still referring to the security module **208** in FIG. 2B, the voice learning module **246** can be configured to learn voices of building occupants and to respond to verbal requests made by the building occupants. The voice learning module **246** can use one or more machine learning models and/or artificial intelligence (AI) techniques, processes, and/or algorithms to identify and associate voices with different occupants in the building. The voice learning module **246** can also use the machine learning models to identify different tones or inflections in the voices that can indicate how the occupants are feeling. For example, if the voice learning module **246** detects an occupant speaking fast, in a high pitched tone, and/or quietly to one or more of the sensor devices **108A-N**, then the voice learning module **246** can determine, by applying one or more machine learning models, that the particular occupant is feeling uncomfortable, concerned, and/or unsafe. Determining how the occupant is feeling can be beneficial to provide more accurate guidance, information, or other types of prompts to the occupant.

[0110] As an illustrative example, if the occupant asks one of the sensor devices **108A-N** whether everything is okay in the building, the voice learning module **246** determines that the occupant is speaking in a panicked, rushed tone, and the security module **208** determines that a security event has occurred at the building, then the security module **208** can determine that the occupant should be provided more comprehensive, step-by-step guidance to help ease the occupant's panic and discomfort. As another example, the occupant can speak to one of the sensor devices **108A-N** by asking for help (e.g., asking for a safest way to exit the building during an emergency and/or saying that they do not know what to do during an emergency) and based on the detected tone and/or inflection in the occupant's voice, the security module **208** can determine an appropriate amount of guidance or other information to provide to the occupant.

[0111] The machine learning models can be trained to identify how the occupant is feeling based on speed at which the occupant speaks, magnitude of spikes in pitch of the occupant's voice, loudness of the occupant's voice, whether the occupant speaks in fluid sentences or whether the occupant's words are choppy or less fluid, etc. Therefore, the machine learning models may identify how the occupant is feeling based on characteristics of the way the occupant speaks rather than actual content or things that the occupant is saying. In other words, the voice learning module **246** may not be actively monitoring what is said by the occupant but rather can passively monitor changes in the way that the occupant speaks in order to determine whether the occupant is comfortable or concerned about current conditions in the building.

[0112] Moreover, the voice learning module **246** can use the machine learning models to learn normal tones or ways of speaking for the building occupants. Therefore, when the occupant speaks to one of the sensor devices **108A-N** and asks for updates on the conditions in the building or asks for guidance, the voice learning module **246** can determine whether the occupant's voice deviates from a known, normal way that the occupant typically speaks. A greater deviation can indicate that the occupant is feeling uncomfortable, insecure, panicked, etc. A greater deviation can therefore indicate that the occupant should be provided with more information or guidance to help calm the occupant.

[0113] Still referring to the security module **208** in FIG. **2B**, the security event detector **248** can be configured to identify a security event from analyzing anomalous signals that are detected by the sensor devices **108A-N** and/or the sensors **112A-N**. As described in reference to FIGS. **1**, **3**, and **4A-B**, the security event detector **248** can receive detected signals from the sensor devices **108A-N** and/or the sensors **112A-N**. The security event detector **248** can retrieve threshold conditions **212A-N** from the building information data store **204** (e.g., refer to FIG. **2A**). The threshold conditions **212A-N** can be determined by the normal conditions determiner **244** and can be based on room or location in the building where the sensor devices **108A-N** are located. The threshold conditions **212A-N** can also be based on general areas or portions of the building (a first floor, a second floor, a kitchen and dining room, a living room, etc.) and/or the building as a whole. The threshold conditions **212A-N** can include light, sound, temperature, motion, and/or visual for each of the designated areas, rooms, locations, and/or sensor devices **108A-N**.

[0114] As described above, the threshold conditions **212A-N** can indicate expected or otherwise normal signal levels for the building (e.g., expected amounts of light in a particular room, expected temperature value and/or temperature range in a kitchen, expected motion or movement near one or more entrances to the building, expected amount of noise in a hallway or other room, etc.). The security event detector **248** can determine whether any of the received signals deviate from the threshold conditions **212A-N** as well as a magnitude and/or duration of the deviation. Based on this analysis, the security event detector **248** can identify whether a security event has occurred. Sometimes, the security event detector **248** can also identify that an emergency, such as a fire, has occurred based on a comparison of the received signals to the threshold conditions **212A-N**.

[0115] The security event detector **248** can also correlate different anomalous signals received at a same or similar time in order to positively identify that the security event occurred. Therefore, the security event detector **248** can improve its accuracy in detection of security events, thereby becoming more reliable to building occupants. Using one or more machine learning models, the security event detector **248** can classify the detected security event. For example, the models can be trained to identify that combinations of certain types of signals and/or deviations in such signals are representative of different types of emergencies. As an illustrative example, the models can be trained to identify a break-in based on a combination of the following signals: a sudden, sharp increase in decibel signals, a sudden increase in movement/motion near a window, door, or other entrance into the building, and video or image feed data depicted shattered glass, debris, or a foreign object entering the building. As another example, the models can be trained to identify a fire based on a combination of the following signals: a sudden and large increase in temperature, detection of smoke, and sporadic shifts in lighting.

[0116] The security event detector **248** can also determine a severity level of the detected security event. One or more machine learning models can be applied to the received and correlated signals in order to assess how severe of a threat the security event poses to building occupants. The security event detector **248** can also determine the severity level based on presence of the occupants in the building. For example, the models can be trained to determine that the security event is of lower severity when none of the occupants are detected as being present in the building. Occupant presence can be determined based on user presence and/or motion sensors positioned throughout the building. Occupant presence can also be determined based on one or more of the sensor devices **108A-N** outputting audio in the building that asks or otherwise prompts present occupants to say something. Occupant presence can also be determined from video and/or image feed data captured by the sensor devices **108A-N**, the sensors **112A-N**, and/or the security system **200**. Moreover, occupant presence can be determined based on pinging, by the centralized hub **102**, the user devices

252A-N of the occupants to determine whether the devices **252A-N** are located within the building and/or connected to a local home network.

[0117] Once the severity level is determined, the security event detector **248** and/or the output generator **250** can determine appropriate guidance or other information to provide to the building occupants. The higher the severity level, the more thorough and/or step-by-step guidance can be provided to the building occupants. The lower the severity level, the less information can be provided to the building occupants.

[0118] Accordingly, the output generator **250** can determine how much information to provide to building occupants, what form of output should be used for that information, and what information should be outputted. For example, if the voice learning module **246** detects that the occupant is panicking, the output generator **250** can determine that more thorough information should be provided to the occupant in order to calm them down. As another example, if the security event detector **248** determines that a burglary has occurred, the output generator **250** can determine that the occupant should receive a notification that there is a burglary and instructions to safely, calmly, and quietly exit the building (e.g., based on and/or using one or more of the escape plans generated by the emergency egress module **206**).

[0119] The output generator **250** can determine an appropriate form of output based on the detected security event. If the security event involves a break-in, for example, the output generator **250** can determine that audio and/or visual output may draw attention to the occupant and therefore put the occupant's safety at increased risk. Thus, the output generator **250** can determine that text messages and/or push notifications transmitted to the user device **252A-N** of the occupant can be a preferred form of output. As another example, if the security event involves a fire, the output generator **250** can determine that audio that is outputted by the sensor devices **108A-N** can be preferred, especially since visual signals may not be seen in smoke and/or through flames. As yet another example, if the centralized hub **102** is unable to connect to any of the user devices **252A-N** of the occupants, then the output generator **250** can select a form of output that can be provided by the sensor devices **108A-N** positioned throughout the building. Similarly, if the centralized hub **102** is unable to connect to one or more of the sensor devices **108A-N**, then the output generator **250** can select a form of output that can be provided by the user devices **252A-N** of the occupants.

[0120] Sometimes, the output generator **250** can also select a preferred form of output based on information about the occupants. For example, if an occupant is deaf, then the output generator **250** can generate visual signals as output to be displayed by the sensor devices **108A-N** (e.g., flashing lights, strobe lights, directional signs projected onto walls, floors, windows, and/or doors, etc.). The output generator **250** can also generate output, such as text messages and/or push notifications, that can be received and viewed by the deaf occupant at their user device **252A-N**.

[0121] The output generator **250** can select a different form of output for each occupant in the building. Output for some occupants can be visual while output for other occupants can be audio. Moreover, output for some occupants can be displayed by the sensor devices **108A-N** while output for other occupants can be displayed by the user devices **252A-N**.

[0122] As mentioned above, the output generator **250** can determine what information should be provided to each occupant. What information to provide can be based on tone of the occupant's voice when they speak to the sensor devices **108A-N**, as described above. What information to provide can also be based on the type of security event, the severity level of the security event, and other information about the occupant. Sometimes, the output generator **250** can generate output that merely mentions that a security event was detected. Sometimes, the output generator **250** can generate output that asks the occupant what type of information they want/need. Based on the occupant's response, the output generator **250** can generate additional or less guidance for the particular occupant. Moreover, sometimes the output generator **250** can generate output that includes guidance to safely and calmly escape the building. How much guidance to provide can be based on a variety of factors, as mentioned above, such as user preference, how the occupant is feeling, what type of security event was detected, and the severity level of the detected security event. Any information

generated by the output generator **250** can then be transmitted to the sensor devices **108A-N** and/or the user devices **252A-N** to be outputted to the occupant(s).

[0123] Referring back to FIG. **2A**, the user devices **252A-N** can include mobile devices such as smartphones, cellphones, laptops, computers, tablets, and/or wearable devices. Building occupants can have user devices **252A-N** that can be in communication with components described herein, such as the sensor devices **108A-N**, the centralized hub **102**, and/or the security system **200**. The user devices **252A-N** can receive notifications (e.g., push notifications at a mobile application), text messages, audio messages, and/or other types of indications about a current state of the building. Sometimes, for example, when a security event is detected, the centralized hub **102** can send a push notification to the user devices **252A-N** of one or more building occupants to make them aware of the security event. As another example, the centralized hub **102** can send egress instructions to the user devices **252A-N** of one or more building occupants to safely guide such occupants to safety. The building occupants can also use the user devices **252A-N** in order to monitor the current state of the building, whether the building occupants are located at the building or remote, and to ask the centralized hub **102** to check on the current state of the building.

[0124] FIG. **3** is a flowchart of a process **300** for detecting a security event in a building. The process **300** can be performed by the centralized hub **102** described herein. More specifically, the process **300** can be performed by one or more components of the security module **208** of the centralized hub **102** (e.g., refer to FIGS. **2A-B**). One or more blocks of the process **300** can also be performed by any of the sensor devices **108A-N**, for example, where one of the sensor devices **108A-N** acts or otherwise operates as the centralized hub **102**, when the centralized hub **102** goes down, and/or when one of the sensor devices **108A-N** identifies a large deviation in an anomalous signal that it detected. The process **300** can also be performed by a variety of other computer systems, networks of computers, servers, and/or devices. For illustrative purposes, the process **300** is described from a perspective of a computer system.

[0125] Referring to the process **300**, the computer system can receive signals from sensors in a building in **302**. As described in reference to FIG. **1**, the computer system can receive the signals at predetermined times, such as every 1 minute, 2 minutes, 3 minutes, 4 minutes, 5 minutes, etc. The computer system can also automatically receive the signals whenever a sensor detects a change in state (e.g., a deviation in passively monitored signals) in the building. Moreover, the computer system can receive the signals upon transmitting requests for any sensed signals from the sensors. Also as described throughout this disclosure, the sensors can include the sensor devices **108A-N** and/or the sensors **112A-N** positioned throughout the building. The received signals can include but are not limited to audio (e.g., decibels), visual (e.g., video feed data, image data), light, motion, temperature, and/or smoke signals.

[0126] The computer system can also retrieve expected threshold conditions in **304**. The computer system can retrieve from a data store expected threshold conditions for each of the received signals. For example, if a light signal is received from a sensor positioned in a kitchen of the building, then the computer system can retrieve the expected threshold condition for light signals in the kitchen of the building. Moreover, the computer system can retrieve the expected threshold conditions for a same or similar timeframe as when the received signals were captured. In the example above, if the light signal is received at 9 pm, then the computer system can retrieve the expected threshold conditions for light in the kitchen at or around 9 pm. Sometimes, the computer system can retrieve overall expected threshold conditions for the building. The overall expected threshold conditions can indicate an average of a particular type of signal or combination of signals that represents a normal state or conditions of the building.

[0127] As described in reference to FIGS. **2A-C**, the computer system can learn normal conditions for the building. These normal conditions can establish expected threshold conditions or ranges for different types of signals that can be sensed in the building. The expected threshold conditions can be learned in a variety of ways. For example, the expected threshold conditions can be learned using statistical analysis over time. The computer system can analyze signal values detected during one or more periods of time (e.g., 8 am to 9 am every morning for a certain number of consecutive days). The

computer system can average, for example, decibel levels during the one or more periods of time, identify spikes or dips in the decibel levels, and categorize those spikes or dips as normal conditions or abnormal conditions. The computer system can also use standard deviations from the historic spread of decibel levels in order to determine expected threshold conditions. In so doing, the computer system can identify typical deviations from the expected threshold conditions that may occur. Any deviation that exceeds the identified typical deviations can be indicative of a security event.

[0128] The expected threshold conditions can also be determined and identified as static values rather than averages, standard deviations, and/or ranges of values. Therefore, if the received signals ever exceed a really high static value in a short amount of time, the received signals can be indicative of a security event. Thus, the computer system can analyze a rate of rise in the received signals to determine whether these signals exceed expected threshold conditions for the building.

[0129] The expected threshold conditions can also be determined and identified based on relativity. In other words, every few minutes, for example, the computer system can receive decibel signals. The computer system can determine an average in decibel level. Over time, the computer system can determine whether the decibel level is increasing and a rate of rise in decibel level relative to the average decibel level. Therefore, a sudden and sharp increase in decibel level relative to the average decibel level during a short timeframe can be indicative of a security event.

[0130] In **306**, the computer system can determine whether any of the received signals exceed the respective expected threshold conditions beyond a threshold level. Sometimes, the computer system can combine the received signals into a collective of signals. The computer system can then determine whether the collective of signals exceeds expected threshold conditions beyond the threshold level. The threshold level can be predetermined by the computer system and based on the type of signal, a location where the signal was detected, a time of day at which the signal was detected, and one or more factors about the building and/or the building occupants. The threshold level can indicate a range of values that, although deviate from the expected threshold conditions, do not deviate so much as to amount to a security event. The threshold level can be greater in locations in the building where typically, or on average, there is more commotion or activity by the building occupants. The threshold level can be lower in locations in the building where typically, or on average, there is less commotion or activity by the building occupants.

[0131] As an illustrative example, temperature signals can have a greater threshold level (e.g., a greater range of expected temperature values) in a bathroom where the temperature can drastically increase when an occupant runs hot water in comparison to a bedroom, where an occupant may only blast A.C. during summer months but otherwise maintain the bedroom at a constant temperature. Therefore, the temperature would have to increase higher and faster in the bathroom than the bedroom in order to trigger identification of a security event.

[0132] As another example, audio signals in a nursery can have a lower threshold level (e.g., a smaller range of expected sound) where typically a young child sleeps in comparison to a family room, which can have a greater threshold level (e.g., a larger range of expected sound) since the occupants typically spend time there, talk, watch TV, and otherwise make a significant amount of noise there. Thus, a lesser deviation in audio signals detected in the nursery can trigger identification of a security event in comparison to the same deviation in audio signals being detected in the family room.

[0133] As yet another example, the expected threshold conditions for anywhere in the building can change depending on the time of day. During nighttime hours when the occupants are typically asleep, any type of signal can have a lower threshold level than during daytime hours when the occupants are going about their daily activities in the building. In other words, during the nighttime, signals that deviate slightly from the expected threshold conditions can be indicative of a security event whereas the same slight deviation may not be indicative of a security event during daytime hours.

[0134] If none of the signals exceed the respective expected threshold conditions beyond the threshold level, then the signals likely indicate normal or otherwise expected conditions in the building. There likely is not a security event. The computer system can return to block **302**.

[0135] If any of the signals exceed the respective expected threshold conditions beyond the threshold level, then the computer system can identify any other signals that were captured at a similar or same time as the signals that exceed the respective expected threshold conditions in **308**. The computer system can then link the identified signals into a security event in **310**. Thus, in **308** and **310**, the computer system can verify that a security event in fact occurred based on analysis of other signals detected throughout the building.

[0136] For example, if an audio signal detected at a front of the building exceeds the respective expected threshold condition beyond the threshold level, then the computer system can also identify an audio signal detected at a back of the building at the same or similar time as the audio signal detected at the front of the building. If the audio signal detected at the back of the building represents a deviation from the expected threshold conditions, albeit a lesser deviation than that of the audio signal detected at the front of the building (e.g., since sound can be more muted farther away from a location of an incident), then the computer system can confirm that the audio signal detected at the front of the building likely constitutes a security event.

[0137] The computer system can also identify different types of signals in **308** that can be linked into a security event in **310**. For example, audio, light, and visual signals can be linked together to paint a story of a security event. One or more other signals can also be correlated or otherwise linked together to verify that the security event occurred and to depict what happened in the security event. Sometimes, the more signals that can be linked to create a robust story of the security event can improve confidence and/or ability of the computer system to detect future security events. For example, the computer system can use one or more machine learning models to learn or otherwise improve the computer system's ability to detect security events from anomalous signals. The security events identified in **310** can be provided as input to the machine learning models in order to improve the computer system.

[0138] Next, the computer system can classify the security event in **312**. As described in reference to FIGS. 2A-C, the computer system can apply one or more machine learning models to the linked signals in order to classify the security event. Classifying the security event can include determining a type of security event (**314**). The computer system can be trained to identify a variety of security event types from different combinations of signals and deviations in signals. The computer system can also be trained to identify the type of security event based on a variety of factors, such as how much the signals deviate from the expected threshold conditions, what type of signals have been detected, where the detected signals were located in the building, whether occupants were present or near the signals when detected, etc.

[0139] Classifying the security event can also include determining a severity level of the security event (**316**). The severity level can be determined based on a variety of factors, including but not limited to the type of security event and how much the signals deviate from the expected threshold conditions. For example, a temperature signal of such magnitude and rapid rise from the expected threshold temperature condition for the building can indicate that a serious issue, such as a fire, has begun in the building. This security event can be assigned a high severity level value. On the other hand, a temperature signal that increases enough to exceed the expected threshold temperature condition over a longer period of time can be identified, by the computer system, as having a lower severity level. The severity level can be a numeric value on a scale, such as between 1 and 100, where 1 is a lowest severity level and 100 is a highest severity level. One or more other scales can be realized and used in the process **300**. The severity level can also be a boolean value and/or a string value.

[0140] The severity level can indicate how much the identified security event poses a threat to the building occupants and/or the building. For example, a higher severity level can be assigned to the identified security event when the event threatens safety of the building occupants, protection of the occupant's personal property, and/or structure of the building. As another example, a lower severity level can be assigned to the event when the event threatens a structure of the building but the occupants are not currently present in the building. Therefore, threats that the security event poses can be weighed against each other in determining the severity level of the security event. As described

in reference to FIGS. 2A-C, the severity level can be determined by the computer system by using one or more machine learning models.

[0141] Moreover, classifying the security event can include determining a location of the security event (318). As described above, the computer system can use one or more machine learning models to determine the location of the security event. The location can be determined based on identifying strength of the received signals and proximity of the received signals from each other. For example, an audio signal received from a front of the building can greatly exceed threshold conditions for the building while an audio signal received from a back of the building can exceed threshold conditions by a smaller magnitude. The computer system can be trained to identify that the security event likely occurred closer to the front of the building rather than the back of the building. The computer system can then compare audio signals and other signals received from locations proximate to the audio signal received from the front of the building in order to narrow down and pinpoint a location of the security event. Using one or more building layouts (e.g., floor plans) and location information for the sensor devices positioned throughout the building that detected the audio signals, the computer system can identify a room or other particular location in the building where the security event occurred. Classifying the security event based on type, severity, and location can be beneficial to determine appropriate guidance, instructions, or other information to provide to building occupants and relevant stakeholders, such as emergency response personnel.

[0142] Once the security event is classified, the computer system can generate appropriate output in 320. Generating the output can include selecting an optimal form of output and determining what information to provide to building occupants or other relevant stakeholders, such as emergency response personnel. Selecting the optimal form of output can be based on the type of security event. For example, if the security event is identified as a burglary, the computer system can determine that audio output, whether provided by the sensor devices or the occupants' mobile devices, can expose the occupants to the burglar and increase an associated security risk. Therefore, the computer system can select forms of output that include visual displays, text messages, and/or push notifications. As another example, if the security event is identified as a fire, the computer system can determine that visual output, as provided by the sensor devices or other sensors in the building, may not be preferred since smoke and flames can make it challenging for the building occupants to view lighted signals. The computer system can select forms of output that may include audio instructions or guidance.

[0143] As described throughout this disclosure, the output can include guidance, instructions, prompts, or information that can be presented via audio, text messages, push notifications, and/or visuals that are displayed in the building. Sometimes the output can alert the building occupant of a security event, such as the type of security event and where it occurred in the building. The output can also include guidance or instructions to assist the building occupant to safely, calmly, and quickly escape the building and avoid the security event. Sometimes, depending on the type and severity level of the security event, the output can include a notification that is automatically transmitted to emergency response personnel, such as police, firefighters, EMTs, etc. Therefore, the building occupants can focus on their own safety and escape from the security event rather than figuring out who to contact.

[0144] Sometimes, the output can include questions that prompt the building occupants to provide some sort of response. Depending on the occupants' response, the computer system can determine what additional information can be provided to the occupants. The computer system can use AR in order to have conversations with the building occupants and act upon those conversations. For example, the computer system can generate output that, when presented by a sensor device, asks the occupant how they are feeling. The occupant can reply that they are concerned, feeling safe, scared, or any other variety of emotions they may be experiencing. The sensor device can transmit the occupant's response to the computer system for further analysis. As described in reference to FIGS. 2A-C, the computer system can learn the occupant's voice and determine a tone and/or inflection of the occupant's voice that can indicate how the occupant is feeling. The computer system can also use one or more semantic analysis techniques in order to detect how the occupant is feeling.

[0145] If the computer system determines that the occupant is in fact feeling concerned or scared, the computer system can generate additional output intended to calm or otherwise assist the occupant is

finding safety. For example, the computer system can contact emergency response personnel upon determining that the occupant is scared for their life. The computer system can also generate step-by-step instructions to help guide the occupant safely out of the building while avoiding a location of the security event.

[0146] If the computer system determines that the occupant is not as concerned or is otherwise feeling relatively safe, the computer system can determine that additional guidance may not be needed for the occupant.

[0147] Regardless of whether a security event is detected, the occupants in the building can converse with the sensor devices. As described throughout, the occupants can ask the sensor devices for updates on current states (e.g., conditions) in the building. The occupants can also tell the sensor devices about updates to the building and/or occupants in the building (e.g., a change in disability or athleticism, moving in of an occupant, moving out of an occupant, birth of a child, death of an occupant, hosting of a dinner party or other social event, going away on a vacation, etc.). Information that the occupant shares with the sensor devices can be transmitted to the computer system, analyzed, and used to update, modify, or improve stored information, emergency escape plans, building layouts, detection of security events, and generation of instructions or guidance.

[0148] Finally, generating the output in **320** can also include transmitting the output to the appropriate devices. The computer system can connect to a home network and poll devices to determine which devices are present in the home network. The computer system can poll devices such as the sensor devices and/or mobile devices of the building occupants. If the devices are determined to be present in the home network, then the computer system can transmit the output locally. If the devices are not present in the home network (e.g., the home network goes down, the occupants and their respective mobile devices are not currently located at the building, a sensor device is offline, etc.), then the computer system can transmit the output over a different network, such as a cellular network or WIFI.

[0149] FIGS. **4A-B** is a flowchart of an example process **400** for detecting a security event from irregular audio signals. Although the process **400** is described in reference to analysis of audio signals, the process **400** can be performed to analyze a variety of other types of signals described throughout this disclosure, including but not limited to light, visual, temperature, and/or motion signals.

[0150] The process **400** can be performed by the centralized hub **102** described herein. More specifically, the process **400** can be performed by one or more components of the security module **208** of the centralized hub **102** (e.g., refer to FIGS. **2A-B**). One or more blocks of the process **400** can also be performed by any of the sensor devices **108A-N**, for example, where one of the sensor devices **108A-N** acts or otherwise operates as the centralized hub **102**, when the centralized hub **102** goes down, and/or when one of the sensor devices **108A-N** identifies a large deviation in an anomalous signal that it detected. The process **400** can also be performed by a variety of other computer systems, networks of computers, servers, and/or devices. For illustrative purposes, the process **300** is described from a perspective of a computer system.

[0151] Referring to the process **400** in both FIGS. **4A-B**, the computer system can receive audio signals from a sensor device in a building in **402**. Refer to FIGS. **1** and **3** for further discussion on receiving signals. The computer system can retrieve expected normal audio conditions for the building in **404**. Refer to block **304** in FIG. **3** for further discussion on retrieving the expected normal audio conditions for the building.

[0152] In **406**, the computer system can determine whether the received audio signal exceeds the expected normal audio conditions beyond a threshold level. Refer to block **306** in FIG. **3** for further discussion. If the audio signal does not deviate from the expected conditions beyond the threshold level, then the computer system can return to block **402** and continue to receive audio signals from one or more sensors in the building, such as the sensor devices. After all, the audio signal can deviate from the expected conditions within a threshold range and still be considered normal. If, on the other hand, the audio signal deviates from the expected conditions beyond the threshold level, then the

computer system can identify a potential security event in the building (**408**). Thus, the received audio signal is abnormal for the building.

[0153] The computer system can accordingly ping other sensor devices and/or sensors in the building for signals captured at a similar time as the audio signal in **410**. The computer system can transmit notifications with timestamps to each of the sensor devices and/or sensors. The notifications can request signals that were captured at the same or similar timestamp as that of the audio signal received in **402**. By requesting signals from other sensor devices and/or sensors, the computer system can correlate signals to determine whether a security event in fact occurred. By correlating the signals, the computer system can also more accurately classify the security event.

[0154] The computer system can receive the other signals from the other sensor devices and/or sensors in **412**. The other signals can be other audio signals like the one that was received in **402**, except the other signals can be detected in other locations in the building. For example, if the audio signal received in block **402** was detected at a front of the building, then the computer system can receive an audio signal from a sensor device located at a back of the building. The other signals can also be any one or more of light, visuals, temperature, smoke, motion, etc.

[0155] The computer system can then retrieve expected normal conditions for each of the other signals (**414**). The expected normal conditions can be retrieved as described in reference to block **404**. Sometimes, the computer system can retrieve an aggregate expected normal condition for the building that represents a combination of the other signals that are received in block **412**.

[0156] In **416**, the computer system can determine whether any of the other signals exceed the respective expected normal conditions beyond a threshold level. Refer to block **406** for further discussion.

[0157] If none of the other signals exceed the respective expected normal conditions beyond the threshold level, then the computer system can return to block **402** and repeat the process **400**. In other words, the computer system can continue to passively monitor the building via the sensor devices and/or sensors. The computer system can continue to receive anomalous signals from the sensor devices and/or sensors that represent different detected conditions in the building.

[0158] If any of the other signals exceed the respective expected normal conditions beyond the threshold level, then the computer system can link those signals with the audio signal **418**. In other words, the computer system can confirm or otherwise verify that a security event was detected. By linking or correlating the signals that exceed expected normal conditions beyond the threshold level during a same or similar timeframe, the computer system can positively identify the security event.

[0159] As described herein, the computer system can classify the linked signals as a security event (**420**). Classifying the security event can include identifying a type of security event, severity level of the security event, and location of the security event. Refer to block **312** in FIG. **3** for further discussion.

[0160] FIG. **5A** is a conceptual diagram of an example scenario where an occupant **502A** verbally requests an update on conditions in building **500** from sensor device **108C**. FIG. **5B** is a conceptual diagram of another example scenario where the occupant **502A** verbally requests an update on conditions in the building **500** from the sensor device **108C**. Referring to both FIGS. **5A-B**, the building **500** can be a home, such as a single family, single story home. The building **500** can also be any other type of home, building, or establishment that can implement egress advisement and safety security systems therein. For example, the building **500** can include an apartment building, a high rise building, a commercial building, and/or a multi-story home. One or more other building configurations are possible.

[0161] The building **500** depicted in both FIGS. **5A-B** includes three rooms: rooms **504A**, **504B**, and **504C**. Each of the rooms **504A**, **504B**, and **504C** have one or more sensor devices **108A-N**. For example, the room **504A** includes sensor devices **108B** and **108N**. The room **504B** includes sensor devices **108A** and **108D**. The room **504C** includes sensor device **108C**. The room **504C** also includes

a door **506** that allows for occupants and other users in the building **500** to enter and exit the building **500**. Although not depicted, the building **500** can include one or more windows, additional sensors, additional or fewer sensor devices **108A-N**, additional doors, additional rooms, and/or additional floors (e.g., levels).

[0162] In the example scenario in FIGS. **5A-B**, the sensor device **108C** can be operating as a centralized hub (e.g., refer to the centralized hub **102** described throughout this disclosure). Sometimes, any of the sensor devices **108A-N** can operate as the centralized hub. Moreover, each of the sensor devices **108A-N** can perform functions of the centralized hub at a same time or at different times without any one of the sensor devices **108A-N** being designated or otherwise appointed as the centralized hub.

[0163] Referring to FIG. **5A**, at time=1, the occupant **502A** is located in the room **504C**. The room **504C** can be an entrance room to the building **500**. A dog **508** can also be located in the room **504C**. At time=1, the dog **508** can be exiting the building **500** through the door **506**. Occupant **502B** is located in the room **504A**, which can be a living room. The occupant **502B** can be watching TV at time=1. Occupant **502C** is in the room **504B**, which can be a kitchen. The occupant **502C** can be cooking a meal in the kitchen at time=1.

[0164] At time=1, the occupant **502A** can ask the sensor device **108C** if everything is okay in the building **500**. For example, the occupant **502A** can speak out loud, "Clarus, is everything ok?" (**510**). The sensor device **108C** can detect the occupant **502A**'s voice (step A). As described throughout this disclosure (e.g., refer to FIGS. **2A-C**), the sensor device **108C** can detect the occupant **502A**'s voice using voice recognition techniques. Using AI and/or AR, the sensor device **108C** can determine what the occupant **502A** is asking the sensor device **108C**. For example, the sensor device **108C** can be trained to understand or detect one or more predetermined commands, such as "Clarus, is everything ok?" Over time, the sensor device **108C** can also learn additional and potentially more nuanced, less direct commands that are said by the occupant **502A** or other occupants in the building **500**. In this example, the sensor device **108C** can detect that the occupant **502A** has spoken a known command, which is asking for a status update on conditions in the building **500**.

[0165] Accordingly, the sensor device **108C** can ping the other sensor devices **108A-N** in the other rooms **504A-504B** for any signal updates. The sensor device **108C** can transmit a notification to the other sensor devices **108A-N** asking the other sensor devices **108A-N** if they detected any anomalous signals over some predetermined period of time. The notification can also request the other sensor devices **108A-N** to provide the sensor device **108C** with any signals that were detected over some predetermined period of time. Moreover, the notification can request the other sensor devices **108A-N** to detect and provide current signals in the rooms **504A-B** at time=1. Therefore, the sensor device **108A** can determine or otherwise identify real-time conditions in the building **500**.

[0166] Each of the other sensor devices **108A-N** can detect signals in their respective rooms **504A** and **504B** (step C). As described above, the other sensor devices **108A-N** can detect real-time signals in the rooms **504A** and **504B**. The other sensor devices **108A-N** can also identify signals in the rooms **504A** and **504B** that had been detected during one or more predetermined time periods that are requested by the sensor device **108C**.

[0167] The other sensor devices **108A-N** can then transmit any of the detected signals to the sensor device **108C** (step D). Sometimes all the sensor devices **108A-N** can transmit detected signals to the sensor device **108C**, even if the detected signals are constant, minimal, or otherwise nonexistent. For example, sensor device **108D** may sense no movement or audio in a location proximate to the sensor device **108D** in the kitchen. Although no movement or audio is detected, the sensor device **108D** can still transmit notification to the sensor device **108C** indicating absence of movement or audio. Sometimes, if any of the sensor devices **108A-N** do not detect any signals, such sensor devices **108A-N** may not transmit signals or any types of notifications to the sensor device **108C** in step D. Thus, the sensor device **108C** may only receive signals that are positively detected by the sensor devices **108A-N** or signals that are detected beyond some threshold level.

[0168] For example, detected motion near an open window that can be attributed to a curtain shifting in a breeze coming through the window may not exceed the threshold level to then be transmitted to the sensor device **108C**. After all, this detected motion may not be serious enough to warrant any type of inquiry into whether the motion is related to a security event or an emergency. On the other hand, swift detected motion through the door **506** in the room **504C** can be transmitted to the sensor device **108C** (if detected by another sensor device or sensor other than the sensor device **108C**) because this movement can exceed the threshold level. This movement can be significant enough to warrant inquiry into whether the movement is related to a security event or an emergency.

[0169] In the example of FIG. **5B**, the sensor device **108C** can detect movement signals in the room **504C**. The sensor device **108C** can detect the dog **508** exiting the building **500** through the door **506**. The sensor device **108C** can also detect audio (e.g., decibel) signals that represent the dog **508**'s footsteps as it exits the building **500** through the door **504C**. If the sensor device **108C** has an image sensor, then the sensor device **108C** can also capture image data of the occupant **502A** standing near the sensor device **108C** and asking the sensor device **108C** if everything is okay in the building **500**. The sensor device **108C** can also capture image data of the dog **508** as the dog exits the building **500** through the door **506**.

[0170] In the room **504A**, the sensor device **108B** can detect audio signals from the TV that is located near the sensor device **108B**. If the sensor device **108B** also includes an image sensor, then the sensor device **108B** can also capture image data of the occupant **502B** sitting in front of the TV and watching TV. The sensor device **108B** can also detect light signals that emanate from the TV or from the occupant **502B** turning off the lights in the room **504A** in order to see the TV better. The sensor device **108B** can also detect no or minimal movement from the occupant **502B**, especially if the occupant **502B** is sitting on the couch watching TV rather than moving around.

[0171] The sensor device **108N** may detect audio signals that are less in magnitude or volume than the audio signals detected by the sensor device **108B** in the room **504A**. The sensor device **108N** can detect more muted or lower volume decibels that represent the same audio from the TV that was detected by the sensor device **108B**. Moreover, like the sensor device **108B**, if the sensor device **108N** has an image sensor, the sensor device **108N** can also capture image data of the occupant **502B** watching the TV.

[0172] In the room **504B**, the sensor device **108A** can detect audio signals of the occupant **502C** moving pots and pans around the kitchen, kitchen utensils and equipment clanging or otherwise making sounds, and/or alarms, clocks, or presets activating on certain kitchen equipment. The sensor device **108A** can also capture image data of the occupant **502C** cooking at the stove. The sensor device **108A** can detect movement of the occupant **502C** as they navigate the kitchen and cook. Moreover, the sensor device **108A** can detect room temperature values near the stove. The sensor device **108A** can also detect smoke near the stove. Sometimes, the sensor device **108A** can also detect changes in light, such as lights turning on for certain kitchen equipment (e.g., a stove light turning on, a microwave light turning off, etc.).

[0173] The sensor device **108D** can detect similar signals as the sensor device **108A** in the room **504B**. For example, the sensor device **108D** can detect audio signals that are of lesser volume and/or magnitude than those signals detected by the sensor device **108A**. This is true if the audio signals originate from a location closer to the sensor device **108A** and farther away from the sensor device **108D**. The sensor device **108D** can also detect different levels and/or magnitudes of movement, temperature, light, and/or image data signals that are also detected by the sensor device **108A**.

[0174] Sometimes, each of the sensor devices **108A** and **108D** can have different sets of signal sensors in order to passively monitor the room **504B**. As an illustrative example, the sensor device **108A** can have temperature, motion, and audio sensors and the sensor device **108D** can have light and image sensors. In this configuration, the sensor device **108D** can capture a full view of the kitchen to detect more accurate light and/or image data signals. Likewise, since the sensor device **108A** is positioned closer to kitchen equipment such as the stove, the sensor device **108A** can capture more accurate temperature, motion, and/or audio signals than the sensor device **108D**. Any other

configurations and/or combinations of signal sensors are possible for the sensor devices **108A** and **108D** in the room **504B** as well as the sensor devices **108B** and **108N** in the room **504A**.

[0175] Still referring to FIG. **5A**, the detected signals described above can be transmitted to the sensor device **108C** in step D. The sensor device **108C** can then determine whether any of the signals exceed expected threshold conditions (step E). The sensor device **108C** can determine whether any of the signals exceed the expected threshold conditions by one or more predetermined amounts (e.g., levels, ranges, values).

[0176] As described in FIGS. **3-4**, the sensor device **108C** can retrieve the expected threshold conditions for signals that can be detected in each of the rooms **504A-504C** and/or the building **500** as a whole. The expected threshold conditions can be based on values that indicate a normal state of each of the rooms **504A-504C** and/or the building **500** as a whole at a particular time that the occupant **502A** asks the sensor device **108C** whether everything is okay in the building **500**.

[0177] As an example, the motion signal representing the dog **508** exiting through the door **506** of the building **500** may not be an expected amount of motion by the door **506** at the particular time that the occupant **502A** wants to know the current state of the building **500**. However, the motion signal representing the dog **508**'s movement may not be significant enough to exceed the expected threshold condition of movement near the door **506** by a predetermined amount. In other words, if the dog **508** sprints out the door **506**, that detected motion can be significant enough to exceed the expected threshold condition by the predetermined amount. However, if the dog **508** merely walks out the door **506**, this movement may not be enough to exceed the expected threshold condition by the predetermined amount, even if the dog **508** exiting through the door **506** is not a normal condition at time=1.

[0178] The sensor device **108C** can determine a status of the building **500** based on determining whether any of the signals exceed the expected threshold conditions (step F). As described in reference to FIGS. **1-4**, the sensor device **108C** can identify a security event when one or more of the signals exceed the expected threshold conditions beyond the predetermined threshold level(s). In the example of FIG. **5A**, the sensor device **108C** can determine that everything is normal in the building **500**. The sensor device **108C** may not detect any security events or emergencies.

[0179] For example, in determining the status of the building **500**, the sensor device **108C** can determine and/or identify what is happening in each of the rooms **504A-504C**. Based on the combination of signals detected in the room **504A**, the sensor device **108C** can determine that the occupant **502B** is merely watching TV and that no irregular activity has been identified in the room **504A**. Similarly, the sensor device **108C** can determine that the occupant **502C** is merely cooking a meal at time=1 in the room **504B**. Although a detected temperature value for the room **504B** may be higher than an average expected temperature for the room **504B** at time=1, the detected temperature value may not exceed the average expected temperature by the threshold amount. If the detected temperature value did exceed the average expected temperature by the threshold amount, then the sensor device **108C** can determine that there may be an emergency in the room **504B**, which can be attributed to a cooking-related fire. Finally, the sensor device **108C** can determine that the dog **508** has exited the room **504C** and gone outside, which, although may not be an expected movement at time=1, may not be enough movement to exceed the expected movement by the threshold amount.

[0180] The sensor device **108C** can output the status of the building (step G). For example, the sensor device **108C** can output an audio message to the occupant **502**. An example audio message can be "Nothing is out of the ordinary" (**512**). Using AI and/or AR, the sensor device **108C** can detect concern in the occupant **502A**'s voice when the occupant **502A** initially requests knowing the status of the building **500**. If the sensor device **108C** detects concern, then the sensor device **108C** can provide additional output to the occupant **502A** in step G in order to ease the occupant **502A**. For example, the sensor device **108C** can output information about what is happening in each of the rooms **504A-504C**. The sensor device **108C** can tell the occupant **502A** what each of the other occupants **502B** and **502C** are doing at time=1.

[0181] Sometimes, when the sensor device **108C** outputs the status of the building in step G, the occupant **502A** can ask follow-up questions. The sensor device **108C** can detect the occupant **502A**'s voice and, using AI, AR, and/or voice recognition techniques, can have a conversation with the occupant **502A**. Having a conversation with the occupant **502A** can include completing operations or tasks that the occupant **502A** asks of the sensor device **108C**. Having a conversation with the occupant **502A** can include providing the occupant **502A** with audio output that responds to the requests made by the occupant **502A**.

[0182] As an illustrative example, after the sensor device **108C** outputs, "Nothing is out of the ordinary" (**512**), the occupant **502A** can ask, "Can you tell me what is happening in the kitchen?" The sensor device **108C** can detect this question and perform actions to generate a response to the question. The sensor device **108C** can access, from a data store, a floor map or other layout information for the building **500** (e.g., refer to FIGS. **2A-C**). The sensor device **108C** can use the floor map to determine which of the rooms **504A-504C** is the kitchen and which of the sensor devices **108A-N** are located within the kitchen. Thus, the sensor device **108C** can determine that the room **504B** is the kitchen and the sensor devices **108A** and **108D** are located therein. The sensor device **108C** can then transmit a notification to the sensor devices **108A** and **108D** with a request for any signals detected at a time (e.g., timestamp) that the sensor device **108C** received the question from the occupant **502A**. The sensor device **108C** can also identify the signals already received from the sensor devices **108A** and **108D** to determine what is happening in the kitchen, instead of requesting new signals from the sensor devices **108A** and **108D**.

[0183] The sensor device **108C** can receive the signals and accordingly determine what is happening in the kitchen. The sensor device **108C** can use AI and/or one or more machine learning models to convert the signals into descriptive events to then be outputted to the occupant **502A**. If, for example, the received signals are image data, then the sensor device **108C** can apply one or more machine learning models to the image data to identify what type of activity is depicted in the image data. The image data can depict the occupant **502C** cooking at the stove, which can be identified by the sensor device **108C** based on application of the one or more machine learning models. Thus, the sensor device **108C** can respond to the occupant **502A** by outputting audio stating, "Someone is cooking in the kitchen." One or more other responses and/or types of responses can be generated and outputted to the occupant **502A**. For example, the outputted response can be in the form of image data or another visual. The image data can be presented at the sensor device **108C**. The image data can also be presented at a mobile device of the occupant **502A**. One or more other variations of responses and output are possible.

[0184] FIG. **5B** depicts the building at time=2. Time=2 can be later than time=1 in FIG. **1**. Time=2 can also be unrelated to time=1 in FIG. **1**.

[0185] At time=2, the dog **508** is outside of the building **500**, the occupant **502A** is still in the room **504C**, the occupant **502B** is still watching TV in the room **504A**, and the occupant **502C** is still cooking in the room **504B**. However, a fire **518** has started in the room **504B** at the stove where the occupant **502C** is cooking. As described throughout this disclosure, one or more of the sensor devices **108A-N**, such as the sensor device **108A** in the room **504B**, can automatically detect an emergency or security event, such as the fire **518**, then determine egress routes for each of the occupants **502A**, **502B**, and **502C** that avoid the detected emergency. However, in the illustrative example of FIG. **5B**, the occupant **502** asks the sensor device **108C** in the room **504C**, "Clarus, is everything ok?" (**514**).

[0186] As described in reference to FIG. **5A**, the sensor device **108C** can detect the occupant **502A**'s voice (step A). Based on detecting the occupant **502A**'s voice, the sensor device **108C** can determine that the occupant **502A** wants an update on what is happening in each of the rooms **504A-504C** in the building **500**. Accordingly, the sensor device **108C** can ping the sensor devices **108A-N** in each of the rooms **504A** and **504B** (step B). Each of the other sensor devices **108A-N** can detect signals in their respective rooms **504A** and **504B** (step C) and transmit such signals to the sensor device **108C** (step D).

[0187] Once the sensor device **108C** receives the signals from the other sensor devices **108A-N**, the sensor device **108C** can determine if any of the signals exceed the expected threshold conditions (step E). If any of the signals do exceed the expected threshold conditions by a threshold level, then the sensor device **108C** can identify an emergency (or other type of security event) in the building (step F). Identifying the emergency can include classifying the emergency, identifying a location of the emergency, and determining a severity level of the emergency (e.g., refer to FIGS. **1-4**).

[0188] In the illustrative example of FIG. **5B**, the sensor device **108C** can receive a temperature signal from the sensor device **108A** in the room **504B** that is great in magnitude, value, and duration. In other words, the received temperature value can be significantly higher than an average expected temperature value for the room **504B** and/or a previously detected temperature value for the room **504B** (e.g., the temperature value at time=1). The received temperature value can therefore exceed the expected threshold condition beyond a predetermined threshold level. The received temperature value can also spike drastically from the previous temperature value for the room **504B** in a short period of time (e.g., in a timeframe that is less than some predetermined threshold period of time). Moreover, the received temperature value can be consistent for more than some predetermined period of time. Because the received temperature value can exceed the expected threshold conditions beyond the threshold amount, the sensor device **108C** can determine that an emergency, such as the fire **518**, has been detected in the room **504B**.

[0189] The sensor device **108C** can receive one or more additional signals that can be used to determine that an emergency exists in the room **504B**. For example, received audio signals can have spikes in decibels that resemble the occupant **502C** screaming, yelling, or otherwise panicking. The sensor device **108C** can be trained using one or more machine learning models and/or AI to detect the concern in the occupant **502C**'s voice and detect an emergency based on such audio signals. Other signals that can be used to detect the fire **518** include smoke signals, motion signals, light signals, and/or image data.

[0190] Once the sensor device **108C** identifies the emergency (step F), the sensor device **108C** can generate emergency guidance for the occupants **502A**, **502B**, and **502C** that are currently located in the building **500** (step G). As described throughout this disclosure (e.g., refer to FIGS. **2A-C**), the sensor device **108C** can retrieve a floor map of the building **500** and predetermined egress escape plans for each of the occupants **502A**, **502B**, and **502C**. Using one or more of AI, predictive analytics, and/or machine learning models, the sensor device **108C** can determine which egress escape plans should be selected for each of the occupants **502A**, **502B**, and **502C**. Selection of the egress escape plans can be based on information about each of the occupants **502A**, **502B**, and **502C** (e.g., age, agility, disability, etc.), locations of the occupants relative to the identified emergency (e.g., egress escape plans can be selected that do not involve passing or going through a location of the emergency), locations of the occupants relative to each other (e.g., the closer together the occupants are, the more likely an egress escape plan can be selected that lets the occupants escape the building together), a predicted or projected spread of the emergency (e.g., egress escape plans that can become obstructed at some point by the spread of the emergency may not be selected), an amount of time remaining before certain egress escape plans can become obstructed by the emergency (e.g., egress escape plans that will become obstructed by the spread of the emergency while the occupant is passing a point along the egress escape plan may not be selected), etc.

[0191] Generating emergency guidance for the occupants **502A**, **502B**, and **502C** can also include selecting an optimal form of output for such guidance. Based on the detected signals from the sensor devices **108A-N** (step C), the sensor device **108C** can determine whether audio and/or visual signals can be outputted to each of the occupants **502A**, **502B**, and **502C**. For example, signals received from the sensor devices **108A** and **108D** can indicate that there is smoke in the room **504B**, so visual signals and guidance may not be seen well by the occupant **502C**. The sensor device **108C** can determine that audio guidance should be outputted by either of the sensor devices **108A** and **108D** and/or text messages, audio, or push notifications should be transmitted to and outputted at a mobile device **524** of the occupant **502C**. Signals received from the sensor devices **108B** and **108N** can indicate that the room **504A** does not have any smoke or bright lights that would make visual signals challenging to see. Therefore, the sensor device **108C** can determine that visual guidance can be

outputted by either of the sensor devices **108B** and **108N** in the room **504A**. The sensor device **108C** can also determine that audio guidance can alternatively or additionally be outputted by either of the sensor devices **108B** and **108N**.

[0192] Once the sensor device **108C** determines and generates appropriate emergency guidance, the sensor device **108C** can transmit the guidance to one or more devices in the rooms **504A**, **504B**, and **504C** where the occupants **502B**, **502A**, and **502C** are located (step H). Therefore, if a room is empty (e.g., no occupants are detected by user detection or motion sensors and/or the sensor devices **108A-N**), then the guidance may not be outputted at device(s) in that room.

[0193] As shown in the illustrative example of FIG. **5B**, the sensor device **108C** can respond to the occupant **502A** by outputting a message that states, "A fire started in the kitchen. Evacuate through the door!" (**516**). The sensor device **108B** in the room **504A** can output audio guidance to the occupant **502B** that states, "A fire started in the kitchen. Leave the room immediately and avoid the kitchen." Although not depicted, the sensor device **108B** and/or **108N** can also output visual signals such as flashing and/or colored lights that are projected on walls and/or floors in a direction that the occupant **502B** can follow to exit the building **500**. The sensor device **108A** in the room **504B** can output audio guidance to the occupant **502C** that states, "Leave the kitchen immediately and exit through the door" (**522**). Although not depicted, the sensor device **108A** and/or **108D** can also output visual signals such as flashing and/or colored lights that are projected on walls and/or floors in a direction that the occupant **502C** can follow to exit the building **500**. Moreover, as shown in FIG. **5B**, a notification can be received at the occupant **502C**'s mobile device **524**. The notification can be a text message, audio guidance, and/or a push notification that prompts and guides the occupant **502C** to safely, quickly, and calmly leave the room **504B**.

[0194] Sometimes, as the occupants **502A**, **502B**, and **502C** egress from the building **500**, the sensor devices **108A-N** can passively monitor the situation to see if the fire **518** gets worse and/or whether the occupants **502A**, **502B**, and **502C** are panicking or otherwise struggling to egress. For example, the sensor devices **108A-N** can use AI techniques to detect panic (e.g., screams, whimpers, crying, etc.) amongst any of the occupants **502A**, **502B**, and **502C** from audio signals. If the sensor devices **108A-N** detect panic, then the sensor devices **108A-N** can generate and output additional guidance intended to ease the panic and fear from any of the occupants **502A**, **502B**, and **502C**.

[0195] If the sensor devices **108A-N** detect any changes to the fire **518** that may affect safe egress of the occupants **502A**, **502B** and **502C**, the sensor devices **108A-N** can generate and output information to that effect to notify the occupants **502A**, **502B**, and **502C**. Any of the sensor devices **108A-N** can also perform a single course correction by selecting or otherwise updating the egress escape plans that were selected for any of the occupants **502A**, **502B**, and **502C**.

[0196] Moreover, based on passive monitoring of the fire **518**, any of the sensor devices **108A-N** can also determine if and when to send notification of the fire **518** to emergency response personnel, such as firefighters, police, and/or EMT. Sometimes, the sensor device **108C** can transmit a notification of the fire **518** to the emergency response personnel upon identifying the emergency in the building (step F). Sometimes, the sensor device **108C** may only transmit the notification to the emergency response personnel based on determining that a detected severity level of the fire **518** exceeds some threshold reporting out level. Furthermore, the sensor device **108C** can transmit the notification to the emergency response personnel after guidance has been outputted to the occupants **502A**, **502B**, and **502C** and based on passive monitoring of the fire **518** as the occupants **502A**, **502B**, and **502C** are egressing from the building **500**.

[0197] Sometimes, the sensor device **108C** as shown in both FIGS. **5A-B** may not be operating as the centralized hub. Therefore, when the sensor device **108C** detects the occupant **502A**'s voice, the sensor device **108C** can transmit the voice signal to a remote computing system, such as the centralized hub **102** described throughout this disclosure. The remote computing system can then perform steps B and E-G instead of the sensor device **108C** performing such steps in FIG. **5A**. Similarly, the remote computing system can perform any of steps B, and E-H in FIG. **5B**. Sometimes, another sensor device in the building **500** can operate as the centralized hub. Accordingly, the sensor

device **108C** can send the voice signal to the sensor device that operates as the centralized hub. That sensor device can then perform steps B and E-G in FIG. **5A** and/or steps B and E-H in FIG. **5B**.

[0198] FIG. **6** depicts example features in a building that include sensor devices **108A-N** integrated therein. As described throughout this disclosure, the sensor devices **108A-N** can include a suite of one or more sensors that can be used to detect conditions in the building. More specifically, the suite of sensors can detect anomalous signals through passive monitoring in locations where the sensor devices **108A-N** are positioned throughout the building.

[0199] The sensor devices **108A-N** can be integrated into one or more existing features in the building. As a result, the sensor devices **108A-N** can be nonobtrusive. The sensor devices **108A-N** also may not detract from aesthetic appearances in the building. Sometimes, the sensor devices **108A-N** can also be standalone devices that can be configured in the building, such as attached to walls, ceilings, placed in corners, and/or plugged into outlets. The sensor devices **108A-N** that are standalone devices can also be simple in design and size such that the sensor devices **108A-N** do not appear obtrusive or diminish aesthetic appearances in the building.

[0200] As shown in FIG. **6**, the sensor devices **108A-N** can be integrated into a variety of existing features in the building. For example, sensor device **108A** can be integrated into a light switch **600**. Integration of the sensor device **108A** herein may not obstruct an ability to flip the light switch **600** on or to operate the light switch **600** as it is intended to be operated. The sensor device **108A** can then detect one or more types of signals in an area surrounding or otherwise proximate to the light switch **600**.

[0201] Sensor device **108B** can be integrated into a wall outlet **602**. Integration of the sensor device **108B** herein may not obstruct an ability to plug power cords into the outlets of the wall outlet **602**. The sensor device **108B** can then detect one or more types of signals in an area surrounding or otherwise proximate to the wall outlet **602**.

[0202] Sensor device **108C** can be integrated into a thermostat **604** in the building. Integration of the sensor device **108C** herein may not obstruct an ability to use any of the control options or display(s) of the thermostat **604**. The sensor device **108C** can then detect one or more types of signals in an area surrounding or otherwise proximate to the thermostat **604**.

[0203] Sensor device **108D** can be integrated into an alert system **606** or other existing security system that is installed in the building. Integration of the sensor device **108D** herein may not obstruct an ability to use any of the control options or display(s) of the alert system **606**. The sensor device **108D** can then detect one or more types of signals in an area surrounding or otherwise proximate to the alert system **606**.

[0204] Sensor device **108N** can be integrated into a lightbulb **608**. Integration of the sensor device **108N** herein may not obstruct an ability to attach the lightbulb **608** to a fixture or otherwise to use the lightbulb **608** for its intended purposes. The sensor device **108N** can then detect one or more types of signals in an area surrounding or otherwise proximate to the lightbulb **608**.

[0205] One or more other integrations of the sensor devices **108A-N** with existing building features are possible.

[0206] FIG. **7** depicts example forms of output that can be generated based on a detected security event. As described throughout this disclosure, the centralized hub **102** and/or any of the sensor devices **108A-N** can select an optimal form of output to provide notifications to occupants in the building. The centralized hub and/or the sensor devices **108A-N** can select the optimal form of output based on a variety of factors.

[0207] For example, output form can be selected based on occupant preferences. Before runtime, the occupant can provide input to the centralized hub **102** indicating that the occupant is deaf and only wants to/can receive text or push notifications to their mobile device and/or visual signals outputted by the sensor devices **108A-N** in the building.

[0208] As another example, output form can be selected based on detection of an occupant's mobile device in the building. If the mobile device is detected in the building, guidance can be outputted there instead of by the sensor devices **108A-N**. This can be beneficial to protect the occupant in situations where a thief or other assailant is in the building since output by the sensor devices **108A-N** can bring the thief's attention to a location where output is provided by the sensor devices **108A-N**, thereby risking the safety of the occupant.

[0209] Output form can also be selected based on location of the occupant relative to the emergency or security event. If the occupant is next to a fire, the occupant may respond quicker and more calmly to loud audio signals rather than flashing lights.

[0210] Output form can also be selected based on severity level of the emergency or security event. If the emergency or security event is very severe, such as a rapidly spreading fire, then output can be generated and presented as audio and visual signals at every mobile device and sensor device **108A-N** in the building. This can ensure that occupants see and follow the guidance wherever they are in the building and that no occupant is left behind. This type of output can also help the occupants to understand the gravity of the situation, which can propel them to egress from the building quicker.

[0211] As another example, output form can be selected based on type of the emergency or security event. If the security event is a burglary, guidance can be outputted as text messages or push notifications to the occupants' mobile devices in order to protect the occupants from being found or tracked down by the burglar. After all, output presented by the sensor devices **108A-N** can attract the burglar's attention to locations of the sensor devices **108A-N**. If the occupants are located where the output is being presented, then the burglar can cross paths with the occupants, thereby putting the occupant's safety at risk.

[0212] As yet another example, output form can be selected based on location of the occupant relative to sensor devices in the building. If the occupant is not located near any sensor device, then the guidance can be transmitted to the occupant's mobile device rather than the sensor devices **108A-N**. On the other hand, if the occupant is located near any of the sensor devices **108A-N** and/or the occupant does not have their mobile device on them, then the guidance can be outputted at the sensor devices **108A-N** closest to the occupant.

[0213] Output form can further be selected based on ambient conditions where the occupant is currently located. If smoke is detected where the occupant is currently located, guidance can be outputted as audio signals instead of visual signals. After all, the smoke can prevent the occupant from seeing the visual signals clear enough.

[0214] FIG. 7 depicts different forms of output that can be selected based on any of the factors listed above. For example, emergency guidance **702** can be presented at a mobile device **700**. The mobile device **700** can be located in the building where the emergency or security event is detected. The centralized hub **102** can, for example, detect that the mobile device **700** is connected to a local home network. The emergency guidance **702** can be presented at the mobile device **700** as a text message, audio message, and/or push notifications for a mobile application. Here, the example emergency guidance **702** states, "Break in detected! Exit your bedroom immediately through the window and do not make much noise . . . the police have been notified and they should arrive soon." The emergency guidance **702** can include additional or less information, based on factors previously described throughout this disclosure (e.g., detected panic of the occupant, type of security event, severity level of the security event, etc.).

[0215] As another example, audio guidance **706** can be outputted by a signaling device **108A** in building **704**. The audio guidance **706** can state, "Fire detected in the kitchen! Exit through the door." The audio guidance **706** can be referring to door **712** in the building **704**. As shown, a sensor strip **710** can also be positioned above the door **712**. The sensor strip **710** can include a plurality of sensors, such as lights, that can be activated by the centralized hub **102** to provide guidance to the occupants when escaping the building **704**. The sensor strip **710** can be any other type of sensor and/or signaling device(s), as described further below in reference to FIGS. 8A-B.

[0216] As yet another example, instead of or in addition to the emergency guidance **702** presented at the mobile device **700** and the audio guidance **706** presented by the sensor device **108A**, the sensor strip **710** can also illuminate to provide visual signals that guide the occupants to exit the building **704**. As described further below, the visual signals presented by the sensor strip **710** can include flashing lights, one steady light, arrows or other indications depicting a direction that the occupants should be moving in, and/or X's or other indications depicting a direction that the occupants should be avoiding. The visual signals can also include colors, such as green signals to demonstrate where it is okay for the occupants to go and red signals to demonstrate where the occupants should not be going.

[0217] FIGS. **8A-B** depict exemplary systems for providing emergency or security event detection, guidance and advisement. In FIG. **8A**, sensor device **108A** of FIGS. **1-2** is used as an example. The sensor device **108A** can be a singular device, as depicted in FIG. **8A**, or it can optionally be spread out physically with separate components that can be in wired or wireless communication with each other (e.g., refer to FIG. **8B**). In the example of FIG. **8A**, the sensor device **108A** includes a light signaling component **830**, an audio signaling component **840**, and a sensor controller **852**. The sensor controller **852** can have a one-to-one ratio of communication. Alternatively, the sensor controller **852** can have a one-to-multiple ratio of communication. The audio signaling component **840** and/or the light signaling component **830** can optionally be integrated into/part of a same housing unit and/or circuit board as each other, the sensor controller **852**, and/or the sensor device **108A** as a whole. Alternatively, each of the components in FIG. **8A**, such as **830**, **840**, and **852**, can be housed separately (e.g., separate devices, such as in reference to FIG. **8B**). The sensor controller **852** can sometimes be in the same housing with the light signaling component **830** while the audio signaling component **840** can be housed separately. Sometimes, the sensor controller **852** and the audio signaling component **840** can share the same housing unit/circuit board while the light signaling component **830** is arranged separately. Moreover, sometimes the components **830** and **840** can be housed in the same unit and the sensor controller **852** can be housed separately.

[0218] In the example of FIG. **8A**, the components **830** and **840** are housed in the same unit as the signaling controller **852**, in the sensor device **108A**. Optionally, the sensor device **108A** can have an external power supply **870** (e.g., lithium battery). The sensor device **108A** can also receive emergency and/or security event signals from the centralized hub **102** or any of the other sensor devices **108A-N** in a building, as described throughout this disclosure. The sensor controller **852** can communicate directly with the light signaling component **830** as well as the audio signaling component **840** in order to provide guidance, instructions, or other information to building occupants about a detected emergency or security event.

[0219] The sensor controller **852** can include a predetermined signaling logic **854**, a predetermined output logic **856**, a temperature sensor **858**, a user presence sensor **860**, a light sensor **866**, a sound sensor **868**, a motion sensor **872**, an image sensor **874**, and a communication interface **862**. The sensor controller **852** can optionally include a power source **864** (e.g., battery) in order to power the sensor controller **852** and/or the sensor device **108A**. Sometimes, the sensor controller **852** may not have one or more of the sensors **858**, **860**, **866**, **868**, **872**, and **874**, and instead can collect sensor information from sensors or other sensor devices **108A-N** positioned throughout the building, as described throughout this disclosure.

[0220] The predetermined signaling logic **854** can select an optimal egress escape route from a list of predetermined egress plans during a real-time emergency or security event (e.g., refer to egress escape plan generation by the emergency egress module **206** in FIGS. **2A-C**). This selection can be based on information sensed in real-time by one or more of the sensors **858**, **860**, **866**, **868**, **872**, and **874**, and/or any other sensors or signaling devices **108A-N** positioned throughout the building.

[0221] Once an egress escape route is selected, the predetermined output logic **856** can determine which form of output should be used to output the egress guidance, as described throughout this disclosure (e.g., refer to the emergency egress module **206** and the security module **208** in FIGS. **2A-C**). Based on the determination of output form, the guidance can be outputted using the light signaling component **830** and/or the audio signaling component **840**. Moreover, if the predetermined output

logic **856** determines that guidance should be outputted by an occupant's mobile device, then the communication interface **862** can transmit guidance instructions to the occupant's mobile device.

[0222] The sensors **858**, **860**, **866**, **868**, **872**, and **874** are described throughout this disclosure (e.g., refer to FIGS. **1-3** and **5A-B**). Briefly, the temperature sensor **858** can be configured to detect changes in temperature in an area proximate to a location of the sensor device **108A**.

[0223] The user presence sensor **860** can determine whether an occupant is located within a room. For example, the user presence sensor **860** can detect human movement (e.g., movement of a limb, walking), human body temperature, and/or human sounds (e.g., breathing, coughing). The user presence sensor **860** can also be configured to detect whether an occupant's mobile device (e.g., smartphone, cellphone, BLUETOOTH headphones, wearable device, etc.) is connected to a local home network. Moreover, the user presence sensor **860** can detect location signals of the occupant's mobile device to determine whether the occupant is located in the room and/or proximate to the location of the sensor device **108A**.

[0224] The light sensor **866** can detect changes in light in an area proximate to the location of the sensor device **108A**. This can include changes in light from lights being turned on and off, lightbulbs suddenly going out, doors being opened or closed, windows being covered, uncovered, and/or broken, movement of furniture or objects that can obstruct light in areas of the room, burning flames from a fire, etc. The light sensor **866** can detect different types of light rays and/or light of varying wavelengths. For example, the light sensor **866** can detect LiDAR, infrared, and/or red lights. The light sensor **866** can also detect changes in light between ambient lighting (e.g., lighting from a window) and LED lighting or other fixture lighting.

[0225] The sound sensor **868** can detect changes in decibels, vibrations, slight sounds, or other anomalous sounds in an area proximate to the location of the sensor device **108A**. The sound sensor **868** may not monitor occupants' conversations. However, the sound sensor **868** can be configured to detect the occupant's voice when the occupant is speaking to the sensor device **108A** (e.g., refer to FIGS. **5A-B**). For example, when the occupant asks the sensor device **108A** for an update on conditions in the building, the sound sensor **868** can detect the occupant's voice so that the sensor device **108A** can respond accordingly.

[0226] The motion sensor **872** can detect movement in an area proximate to the location of the sensor device **108A**. For example, the motion sensor **872** can detect slight movements (e.g., a curtain moving in a breeze from an open window) as well as rapid, fast, or otherwise unexpected movements (e.g., a child or pet running through a room). Sometimes, the motion sensor **872** can be the same as the user presence sensor **860**. Sometimes, the sensors **872** and **860** can be separate, as shown in FIG. **8A**.

[0227] The image sensor **874** can capture image data of an area proximate to the location of the sensor device **108A**. The image sensor **874** may not actively monitor activity in a room. Instead, the image sensor **874** can be triggered, by the sensor controller **852**, to activate and capture image data of the room. For example, as depicted in FIGS. **5A-B**, when the sensor device **108C** detects the occupant **502A** asking for a status update on the building **500**, the sensor device **108C** can ping other sensor devices, such as the sensor device **108A**, and request one or more types of sensor signals. The one or more types of sensor signals can include image data. Thus, upon receiving the request, the sensor device **108A** can capture image data of the room **504B**. Otherwise, the sensor device **108A** may not continuously capture image data of the room **504B**. This is beneficial to ensure and protect occupant privacy. The image data can include video feeds and/or still images.

[0228] The communication interface **862** can facilitate communication (e.g., wired or wireless) with the other components, **830** and **840**, comprising the sensor device **108A**. The communication interface **862** can also facilitate communication between the sensor device **108A**, the centralized hub **102**, other sensor devices **108A-N**, sensors, and/or security system of the building.

[0229] The light signaling component **830** can include a light source **832**, a controller **834**, a communication interface **836**, and an optional power source **838**. The light source **832** can be any

form of lighting, including but not limited to an LED light strip (e.g., refer to FIGS. 7 and 8B). The light source **832** can emit different colors, patterns, symbols based on guidance or other signaling instructions communicated to the light signaling component **830** by the sensor controller **852**. The controller **834** can be configured to activate the light source **832** based on receiving an activation signal/instruction from the sensor controller **852**. The communication interface **836** can allow the light signaling component **830** to communicate with the sensor controller **852** and/or one or more other components of the sensor device **108A**. As mentioned, the power source **838** can power the light signaling component **830**. Sometimes, the light signaling component **830** may not include the power source **838** and can instead rely on power from the external power supply **870** that provides power to the sensor device **108A** as a whole.

[0230] The audio signaling component **840** can include a speaker **842**, a controller **844**, a communication interface **846**, stored audio signals **848**, and an optional power source **850**. The speaker **842** can be any form or mechanism to output audio cues/instructions (e.g., refer to FIGS. 7 and 8B). The speaker **842** can emit audio/verbal instructions to an occupant in the building based on signaling instructions communicated to the audio signaling component **840** by the sensor controller **852**. The controller **844** can be configured to activate the speaker **842** based on receiving an activation signal/instruction from the sensor controller **852**. The communication interface **846** can allow the audio signaling component **840** to communicate with the sensor controller **852** and/or any other components of the sensor device **108A**.

[0231] The stored audio signals **848** can include a plurality of verbal instructions that are associated with each possible egress escape plan out of a room that the sensor device **108A** is located in. Therefore, when the sensor controller **852** transmits an activation signal to the audio signaling component **840**, the activation signal can indicate which of the stored audio signals from the stored audio signals **848** should be played. Then, the controller **844** can activate the speaker **842** by having the speaker output the selected audio signals from the stored audio signals **848**. As mentioned, the power source **850** can power the audio signaling component **840**. Sometimes, the audio signaling component **840** may not include the power source **850** and can instead rely on power from the external power supply **870** that provides power to the sensor device **108A** as a whole.

[0232] FIG. 8B depicts an example system for providing emergency guidance and advisement. In this example room **800**, a door **802** is fitted with a first LED strip **812**. The first LED strip **812** can be attached on top of a molding of the door **802** or anywhere else along a perimeter of the door **802**. A window **804** is also fitted with a second LED strip **810**, which can be attached on top of a molding of the window **804** or anywhere else along a perimeter of the window **804**. This way, the first and second LED strips **812** and **810** are not visible to an occupant or at least are not prominently displayed in the room **800**.

[0233] In this example, sensor device **108A** is also configured to a wall of the room **800**. The sensor device **108A** can be retrofitted into an existing socket in the wall. As described throughout this disclosure (e.g., refer to FIG. 6), the sensor device **108A** can be a plug-in that is inputted into an outlet in the room **800** or otherwise integrated into any other existing features in the room **800**. Here, the sensor device **108A** supports audio output. Thus, the sensor device **108A** communicates with the first and second LED strips **812** and **810** to display additional and/or alternative signals to an occupant during an emergency or security event. The sensor device **108A** can also communicate with a mobile device of the occupant (not depicted) to provide guidance or other instructions during the emergency or security event. The strips **812** and **810** and the sensor device **108A** can communicate through a wired and/or wireless connection, as previously discussed throughout this disclosure, wherein a communication signal (e.g., activation signal) between the sensor device **108A** and the first LED strip **812** is signal **820B** and a communication signal between the sensor device **108A** and the second LED strip **810** is signal **820A**. During an emergency or security event and once the sensor device **108A** selects an optimal egress escape plan, the sensor device **108A** can communicate visual signaling instructions to the first and/or second LED strips **812** and **810** via the signals **820B** and **820A**, respectively.

[0234] For example, if the selected egress escape plan requires the occupant to exit through the door **802**, the sensor device **108A** can prompt (e.g., send an activating signal to) the first LED strip **812** to turn green, depict arrows, and/or flash. The sensor device **108A** can also prompt the second LED strip **810** to turn red and/or depict “X” signals so that the occupant understands not to exit through the window **804**. The sensor device **108A** can optionally, additionally, or alternatively output audio messages instructing the occupant about how to exit the room **800**.

[0235] Moreover, the sensor device **108A** can communicate with lights **814** in the room **800** via signal **820C**. Sometimes, the room **800** may not include the first and second LED strips **812** and **810**. Instead, the sensor device **108A** can communicate with existing features in the room **800** to provide guidance to occupants located therein. For example, the sensor device **108A** can transmit light signaling instructions to the light **814** via the signal **820C**. The instructions can cause the light **814** to turn on, off, flash, etc. The light **814** can therefore assist in guiding the occupant to safely exit the room **800**. The sensor device **108A** can also communicate with one or more other existing features in the room **800**, including but not limited to TVs, display screens, thermostats, alert/security systems, and smart appliances (e.g., stove, microwave) to provide guidance, instructions, or other notifications to the occupants located therein.

[0236] FIG. **9** is an example apparatus **900** for providing emergency and/or security guidance and advisement in accordance with the present disclosure. In this example, the apparatus **900** is configured as an electrical power outlet that includes one or more receptacles **901**. The apparatus **900** is configured to include a sensor device **902** (e.g., the sensor devices **108A-N**), an emergency and security event detector **904**, a communication device **906**, a speaker **908**, and a display device **910**. In other examples, the apparatus **900** can include one or more other components described throughout this disclosure. For example, the apparatus **900** can include only the sensor device **906**, which can include one or more of the components described in reference to the sensor devices **108A-N** throughout this disclosure (e.g., refer to FIGS. **2A-C**). The apparatus **900** can also include components such as the emergency egress module **206** and/or the security module **208** depicted and described in reference to FIG. **2B**. The apparatus **900** can further include one or more of the sensors described throughout this disclosure, such as the sensors depicted and described in reference to FIG. **8A**. Various configurations of the apparatus **900** are possible.

[0237] The sensor device **902** can include a suite of sensors, as described throughout this disclosure, that can be configured to detect different types of signals in an area proximate to the location of the apparatus **900**. Sensed signals can be recorded locally in the apparatus **900** and/or in one or more remote computing devices, such as the centralized hub **102** (e.g., refer to FIGS. **1-2**). As described herein, the user detector **602** can be of various types, such as motion sensors and cameras.

[0238] The emergency and security event detector **904** can be configured to detect information about an emergency or security event. The emergency and security event detector **904** can be part of the sensor device **902** or can be separate. For example, signals can be detected by the sensor device **902** and transmitted to the emergency and security event detector **904**. The emergency and security event detector **904** can then analyze the signals and determine whether the signals indicate that an emergency or security event is occurring in the building.

[0239] The communication device **906** is included in the apparatus **900** and configured to enable data communication with the centralized hub **102** and/or other computing devices, sensor devices, and/or sensors positioned throughout the building. The communication device **906** can include a wireless and/or wired data communication interface.

[0240] The speaker **908** operates to generate sounds, such as audible cues, horns, or verbal messages for egress guidance and instructions. The speaker **908** can also provide updates to the occupants about current conditions in the building. For example, when an occupant asks the apparatus **900** for an update on what is happening in the building, status information can be outputted by the speaker **908**. The speaker **908** can also be used to supplement other fixed audio devices or act as a substitute if fixed audio devices are not functioning in the building. Such sounds can complement

visual signs in emergencies where smoke intensity can diminish or preclude the ability to see the visual signs.

[0241] The display device **910** operates to display visual signs that can guide an occupant along an exit route. In some examples, the display device **910** includes a display screen that is provided in the apparatus **900** and displays information with visual signs thereon. In addition or alternatively, the display device **910** operates as a projector that projects a lighted sign on another object, such as a wall, a floor, or a ceiling. In the illustrated example, the display device **910** projects a lighted arrow on the floor to guide the occupant in a direction to exit.

[0242] FIG. **10** is another example apparatus **930** for providing emergency and/or security guidance and advisement in accordance with this present disclosure. The apparatus **930** is configured similar to the apparatus **900** except that the apparatus **930** is implemented as an electrical switch having a switch button **932**. Similarly to the apparatus **900**, the apparatus **930** can include at least one of the sensor device **902**, the emergency and security event detector **904**, the communication device **906**, the speaker **908**, and the display device **910**. As the apparatus **930** is similar to the apparatus **900**, the description of the apparatus **900** is incorporated by reference with respect to the apparatus **930**.

[0243] FIG. **11** is a conceptual diagram depicting a building **1100** with sensor devices positioned throughout that provide guidance and prompts to building occupants during an identified emergency. The guidance and prompts described in reference to FIG. **11** can be determined by the centralized hub **102**. More specifically, the emergency egress module **206** of the centralized hub **102** can determine appropriate guidance and/or prompts for the building occupants based on detected conditions in the building **1100**. The guidance and/or prompts described in reference to FIG. **11** can also be determined by the emergency egress module **206** and applied to security events such as break-ins and burglaries, as detected and determined by the security module **208**. For illustrative purposes, the guidance and prompts determined by the emergency egress module **206** are described in relation to a fire emergency in the building.

[0244] The building **1100** can be a house that includes a lower level **1102** and a stairway **1104** that goes to an upper level. The upper level includes a hallway **1105**, a first bedroom **1106**, and a second bedroom **1108**. A centralized hub **1110** (e.g., the centralized hub **102** described in reference to FIGS. **1-2**) has determined a floor map **1112** that maps pathways within the building **1100**. The floor map **1112** may have been determined from motion detection information obtained by detecting motion of occupants as they moved throughout the building **1100**. The floor map **1112** can also be determined as described in reference to the emergency egress module **206** in FIG. **2B**. Sensor devices **1114**, **1116**, **1118**, **1120**, **1124**, and **1126** can also be placed in each of the rooms or locations **1102**, **1105**, **1106**, and **1108** in the building **1100**. The sensor devices **1114**, **1116**, **1118**, **1120**, **1124**, and **1126** can be connected to the centralized hub **1110**, through one or more wired and/or wireless connections.

[0245] The building **200** can include various additional sensor devices, such as smart thermostat devices, that can detect different types of signals in the building **200** and communicate other information to the centralized hub **102**, as described throughout this disclosure (e.g., refer to FIGS. **1-2**).

[0246] In general, devices that communicate with the centralized hub **1110** can include one or more of a smart thermostat, smoke detector, smart outlet covers, sensors, and sensor devices located, e.g., on doors and windows or in other locations in the building **200**. A given device may provide one function or multiple functions (e.g., a smart outlet cover may include a motion detector as well as one or more additional sensors).

[0247] Although one centralized hub **1110** is shown, multiple monitoring devices may be included in the building **1100**, such as one monitoring device per room. Each of the monitoring devices can operate similarly to the centralized hub **1110**. For example, each of the monitoring devices can take turns performing functions of the centralized hub **1110** (e.g., refer to the centralized hub **102** in FIG. **2B**). As another example, each of the sensor devices **1114**, **1116**, **1118**, **1120**, **1124**, and **1126** can take turns performing functions of the centralized hub **1110**. Moreover, a smart thermostat, existing

alert system, smoke detector, or other devices in the building **1100** can also be secondary monitoring systems. A secondary monitoring system (and the centralized hub **1110**) can include various sensors (e.g., for audio, light, temperature, fire, smoke, motion detection, etc.) and/or can communicate with other sensors included in an area monitored by the respective monitoring device.

[0248] In some implementations, the centralized hub **1110** can be a master monitoring system and other monitoring devices, such as the sensor devices **1114**, **1116**, **1118**, **1120**, **1124**, and **1126** can be secondary monitoring systems. In some implementations, each secondary monitoring system can take over control as a new master monitoring system if the centralized hub **1110** is out of commission (e.g., consumed by fire), as described above. A new master monitoring system can operate using last-received information from the centralized hub **1110** and information received from other secondary monitoring systems. In some implementations, all monitoring systems located in the building **1100** can act as peer devices (e.g., pre-emergency and/or during an emergency), with no device designated as a master monitoring device.

[0249] As mentioned, devices included in the building **1100** can connect to the centralized hub **1110** using one or more wired or wireless connections. Additionally or alternatively, devices in the building **1100** can connect to a cloud based service, to upload information and download information provided by other devices, so that a given device can send and receive data even if in a home network is compromised, e.g., by some type of emergency. For example, during a disaster, devices may not be able to communicate on a local network, but a smart thermostat in one room and the centralized hub **1110** may each be able to communicate with the cloud service (e.g., using a cellular network) and thereby exchange information with each other, using the cloud service as an intermediary.

[0250] Various devices, e.g., secondary monitoring systems or other devices that include motion detection, such as the sensor devices **1114**, **1116**, **1118**, **1120**, **1124**, and **1126**, can provide motion detection information to the centralized hub **1110** and/or to secondary monitoring system(s). Each motion detection device can have a known location within the building **1100**, and can provide a device identifier along with provided motion detection information. The centralized hub **1110** can use the received motion detection information to determine the floor map **1112** of the building **1100**. The floor map **1112** indicates paths into and out of the building **1100**, and paths into and out of respective rooms or on the stairway **1104**.

[0251] The motion detection information can indicate the paths that occupants frequently use while moving within the building **1100**. Paths can be identified by time and location of detected motion, as well as direction of motion as indicated by successive motion detection data points. For example, first, second and third motion sensors may detect motion at first, second, and third time points that are one second apart, indicating that a user moved between locations associated with the first, second, and third motion sensors. Frequency of movement, over time, can indicate main paths throughout the building **1100**. For example, motion detectors may detect occasional movement of an occupant in a corner of a room (e.g., by a dresser), but may more often detect movement of occupants in hallways, through doorways, on stairs, etc. The centralized hub **1110** may know which sensors are in proximity to doors (e.g., room doors, exit doors) and windows, and can identify paths that lead into and out of rooms and out of the building **1100**.

[0252] Sensors can also be located on doors and/or windows. The centralized hub **1110** can determine an exit path by detecting movement of an occupant towards a door and then opening of that door. As a similar example, the centralized hub **1110** can detect a path that includes an exit by detecting the opening of a door when an occupant enters, and then detecting continuous movement of the occupant through the building **1100** to a location within the building. The centralized hub **1110** can identify path segments within the building **1100** that interconnect and that lead to an exit (e.g., door, window).

[0253] During runtime, the centralized hub **1110** (or a secondary monitoring system) can receive information that indicates a presence of an emergency within the building **1100**. For example, the centralized hub **1110** can receive (or can generate) information that indicates the presence of a fire **1128** on the lower level **1102** of the building **1100**. The presence of the fire **1128** can be determined,

for example, based on one or more received temperature readings being more than a threshold temperature. As another example, the centralized hub **1110** can receive a fire indication signal from one or more smoke detection devices. Other fire detection approaches can include IR (Infra-Red) fire detection and rate of rise temperature detection. Fire indication information can indicate which location(s) in the building **1100** are on fire (or sufficiently close to a fire so as to be avoided by occupants of the building **1100**).

[0254] The centralized hub **1110** can determine, based on the floor map **1112** and the received fire indication information, one or more exit routes that can be used by occupants to exit the building **1100**. The exit routes can include portions of the floor map **1112** that avoid the locations within the building **1100** that have been identified as locations to be avoided. For example, based on the location of the fire **1128** being on the left side of the building **1100**, the centralized hub **1110** can determine that the stairs **1104** are currently usable. Accordingly, the centralized hub **1110** can determine an exit path that routes upstairs occupants down the stairs **1104** and out a front door **1130**.

[0255] After determining the exit route(s), the centralized hub **1110** can generate and send signaling instructions to various sensor devices located in the building **1100**, for the sensor devices to emit signal(s) to guide the occupant to an exit route that will safely lead the occupant out of the building **1100**. For example, the centralized hub **1110** can send audio and/or visual signaling instructions to one or more of the sensor devices **1114**, **1116**, **1118**, **1120**, **1124**, and **1126**.

[0256] Sensor devices **1114**, **1116**, **1118**, **1120**, **1124**, and **1126** can emit multi-colored, strobing, LED (Light Emitting Diode) laser light, and can be mounted low, at exit points (e.g., door, window) in each room. LED guiding lights, can be mounted low in outlet-type components, in pathways leading to egresses from the building **1100**. Sensor devices **1114**, **1116**, **1118**, **1120**, **1124**, and **1126** can emit various audio and visual cues to the occupant, for example. For instance, sensor devices **1114**, **1116**, **1118**, **1120**, **1124**, and **1126** can include flashing lights that may indicate a direction an occupant is to take to proceed to (or stay one) an exit route. A series of flashing lights (e.g., in a hallway) may indicate a presence and direction of an exit route. Sensor devices **1114**, **1116**, **1118**, **1120**, **1124**, and **1126** can also be placed onto doors and/or windows, to indicate presence of respective doors and windows, and to indicate whether a given door or window is part of an exit route. Different colors can indicate inclusion or exclusion of a given door, window, or pathway on an exit route. For example, a flashing red signal (e.g., a red "X") on a doorway may indicate that the doorway is to be avoided (and the door kept shut). A flashing green light may indicate that the given door, window, or path segment is part of the exit route.

[0257] Sensor devices **1114**, **1116**, **1118**, **1120**, **1124**, and **1126** can be configured to play audio instructions for an occupant, for providing directional guidance towards egresses, as described herein. Audio instructions can include a fire status description (e.g., "a fire has been detected downstairs"), directional clues (e.g., "go out of the door and to your left"), or more detailed instructions (e.g., "place a wet towel under the door and leave the door closed"). Audio instructions can be specific to the particular room where the occupant is located, based on the location of the room, the location of the detected fire, a determined exit route, and potential detected levels of concern, panic, or uncertainty of the occupant (e.g., refer to the centralized hub **102** in FIG. 2B).

[0258] For the particular example of the fire **1128** located in the left of the lower level **1102**, the centralized hub **1110** can emit a lighted directional signal and an audio instruction **1132** directing occupants located in the lower level **1102** to proceed to and exit the front door **1130**. Signaling instructions can be sent from the centralized hub **1110** to the sensor device **1118** located near an entry to the lower level **1102**, for the sensor device **1118** to play an audio instruction **1136** directing the occupant to not enter the lower level **1102**.

[0259] Signaling instructions can also be sent from the centralized hub **1110** to sensor devices **1124** and **1126** located in the room **1106**, for the sensor devices **1124** and **1126** to direct occupants located in the room **1106** out of the building **1100**. For example, the sensor devices **1124** and **1126** can emit lighted arrows that direct the occupant to a bedroom door **1136** and out of the room **1106**. Sensor devices located on or near the bedroom door **1136** (e.g., a sensor device **1137**) can emit, in response

to received instructions, signals (e.g., lighted) indicating the presence of the bedroom door **1136** and that the occupant is to go through the bedroom door **1136**. Sensor devices located on or near windows **1138** and **1140** can emit, in response to received instructions, signals (e.g., lighted) indicating that the windows **1138** and **1140** are not part of a recommended exit route. The sensor device **1126** (or another device) can, in response to a received instruction, emit an audio instruction **1142** that directs occupants in the room **1106** to exit the room **1106** and proceed to the stairs **1103**. The device **1122**, located in the hallway **1105**, can emit a lighted arrow directing users down the hallway **1105** and audio instructions **1144** that directs the occupants to the stairs **1103**. The device **1114**, also located in the hallway **1105**, can emit audio instructions **1134** that directs the occupants down the stairs **1103** and to exit through the front door **1130**.

[0260] Signaling instructions similar to those sent to sensor devices **1124** and **1126** in the room **1106** can also be sent to sensor devices **1120** and **1126** in the room **1108**. Signals emitted by sensor devices **1120** and **1126** in the room **1108**, including an audio instruction **1146** played by the sensor device **1120**, can direct occupants out of the room **1108** (e.g., through a door **1147** and down the stairs **1103**), rather than out a window **1148** or a window **1150**.

[0261] Other types of signaling instructions and corresponding signals can be generated in the building **1100**. For example, information can be sent to mobile devices of occupants of the building **1100** that direct the occupants to and on the determined exit routes. The centralized hub **1110**, secondary monitoring systems, and/or an application running on a mobile device may know where the mobile device (and associated occupant) are located within the building **1100**, with respect to the fire and the determined exit routes. Such knowledge can be used to tailor instructions that are sent to and displayed (or played) on a given mobile device.

[0262] Other devices in the building may receive and present information related to the fire **1128** and recommended evacuation of the building **1100**. For example, the centralized hub **1110** can communicate with various computing devices or displays located within the building **1100**. For example, the centralized hub **1110** can send information or signaling instructions to one or more desktop computing devices, smart televisions, or other devices located within the building **1100**. The computing devices can be configured to display information (e.g., a fire warning, exit route information), based on information received from the centralized hub **1110**. In some implementations, the centralized hub **1110** can remotely control (e.g., turn on) devices that include a display, and instruct the devices to display (and/or play) information useful for evacuation of the building **1100**, such as exit route information that is specific to the location of the fire **1128** and the location of the respective device (e.g., a smart television in the lower level **1102** may display different information from a smart television in the room **1108**).

[0263] FIG. **12** shows an example of a computing device **1200** and an example of a mobile computing device that can be used to implement the techniques described here. The computing device **1200** is intended to represent various forms of digital computers, such as laptops, desktops, workstations, personal digital assistants, servers, blade servers, mainframes, and other appropriate computers. The mobile computing device is intended to represent various forms of mobile devices, such as personal digital assistants, cellular telephones, smart-phones, and other similar computing devices. The components shown here, their connections and relationships, and their functions, are meant to be exemplary only, and are not meant to limit implementations of the inventions described and/or claimed in this document.

[0264] The computing device **1200** includes a processor **1202**, a memory **1204**, a storage device **1206**, a high-speed interface **1208** connecting to the memory **1204** and multiple high-speed expansion ports **1210**, and a low-speed interface **1212** connecting to a low-speed expansion port **1214** and the storage device **1206**. Each of the processor **1202**, the memory **1204**, the storage device **1206**, the high-speed interface **1208**, the high-speed expansion ports **1210**, and the low-speed interface **1212**, are interconnected using various busses, and can be mounted on a common motherboard or in other manners as appropriate. The processor **1202** can process instructions for execution within the computing device **1200**, including instructions stored in the memory **1204** or on the storage device **1206** to display graphical information for a GUI on an external input/output device, such as a display

1216 coupled to the high-speed interface **1208**. In other implementations, multiple processors and/or multiple buses can be used, as appropriate, along with multiple memories and types of memory. Also, multiple computing devices can be connected, with each device providing portions of the necessary operations (e.g., as a server bank, a group of blade servers, or a multi-processor system).

[0265] The memory **1204** stores information within the computing device **1200**. In some implementations, the memory **1204** is a volatile memory unit or units. In some implementations, the memory **1204** is a non-volatile memory unit or units. The memory **1204** can also be another form of computer-readable medium, such as a magnetic or optical disk.

[0266] The storage device **1206** is capable of providing mass storage for the computing device **1200**. In some implementations, the storage device **1206** can be or contain a computer-readable medium, such as a floppy disk device, a hard disk device, an optical disk device, or a tape device, a flash memory or other similar solid state memory device, or an array of devices, including devices in a storage area network or other configurations. A computer program product can be tangibly embodied in an information carrier. The computer program product can also contain instructions that, when executed, perform one or more methods, such as those described above. The computer program product can also be tangibly embodied in a computer- or machine-readable medium, such as the memory **1204**, the storage device **1206**, or memory on the processor **1202**.

[0267] The high-speed interface **1208** manages bandwidth-intensive operations for the computing device **1200**, while the low-speed interface **1212** manages lower bandwidth-intensive operations. Such allocation of functions is exemplary only. In some implementations, the high-speed interface **1208** is coupled to the memory **1204**, the display **1216** (e.g., through a graphics processor or accelerator), and to the high-speed expansion ports **1210**, which can accept various expansion cards (not shown). In the implementation, the low-speed interface **1212** is coupled to the storage device **1206** and the low-speed expansion port **1214**. The low-speed expansion port **1214**, which can include various communication ports (e.g., USB, Bluetooth, Ethernet, wireless Ethernet) can be coupled to one or more input/output devices, such as a keyboard, a pointing device, a scanner, or a networking device such as a switch or router, e.g., through a network adapter.

[0268] The computing device **1200** can be implemented in a number of different forms, as shown in the figure. For example, it can be implemented as a standard server **1220**, or multiple times in a group of such servers. In addition, it can be implemented in a personal computer such as a laptop computer **1222**. It can also be implemented as part of a rack server system **1224**. Alternatively, components from the computing device **1200** can be combined with other components in a mobile device (not shown), such as a mobile computing device **1250**. Each of such devices can contain one or more of the computing device **1200** and the mobile computing device **1250**, and an entire system can be made up of multiple computing devices communicating with each other.

[0269] The mobile computing device **1250** includes a processor **1252**, a memory **1264**, an input/output device such as a display **1254**, a communication interface **1266**, and a transceiver **1268**, among other components. The mobile computing device **1250** can also be provided with a storage device, such as a micro-drive or other device, to provide additional storage. Each of the processor **1252**, the memory **1264**, the display **1254**, the communication interface **1266**, and the transceiver **1268**, are interconnected using various buses, and several of the components can be mounted on a common motherboard or in other manners as appropriate.

[0270] The processor **1252** can execute instructions within the mobile computing device **1250**, including instructions stored in the memory **1264**. The processor **1252** can be implemented as a chipset of chips that include separate and multiple analog and digital processors. The processor **1252** can provide, for example, for coordination of the other components of the mobile computing device **1250**, such as control of user interfaces, applications run by the mobile computing device **1250**, and wireless communication by the mobile computing device **1250**.

[0271] The processor **1252** can communicate with a user through a control interface **1258** and a display interface **1256** coupled to the display **1254**. The display **1254** can be, for example, a TFT

(Thin-Film-Transistor Liquid Crystal Display) display or an OLED (Organic Light Emitting Diode) display, or other appropriate display technology. The display interface **1256** can comprise appropriate circuitry for driving the display **1254** to present graphical and other information to a user. The control interface **1258** can receive commands from a user and convert them for submission to the processor **1252**. In addition, an external interface **1262** can provide communication with the processor **1252**, so as to enable near area communication of the mobile computing device **1250** with other devices. The external interface **1262** can provide, for example, for wired communication in some implementations, or for wireless communication in other implementations, and multiple interfaces can also be used.

[0272] The memory **1264** stores information within the mobile computing device **1250**. The memory **1264** can be implemented as one or more of a computer-readable medium or media, a volatile memory unit or units, or a non-volatile memory unit or units. An expansion memory **1274** can also be provided and connected to the mobile computing device **1250** through an expansion interface **1272**, which can include, for example, a SIMM (Single In Line Memory Module) card interface. The expansion memory **1274** can provide extra storage space for the mobile computing device **1250**, or can also store applications or other information for the mobile computing device **1250**. Specifically, the expansion memory **1274** can include instructions to carry out or supplement the processes described above, and can include secure information also. Thus, for example, the expansion memory **1274** can be provide as a security module for the mobile computing device **1250**, and can be programmed with instructions that permit secure use of the mobile computing device **1250**. In addition, secure applications can be provided via the SIMM cards, along with additional information, such as placing identifying information on the SIMM card in a non-hackable manner.

[0273] The memory can include, for example, flash memory and/or NVRAM memory (non-volatile random access memory), as discussed below. In some implementations, a computer program product is tangibly embodied in an information carrier. The computer program product contains instructions that, when executed, perform one or more methods, such as those described above. The computer program product can be a computer- or machine-readable medium, such as the memory **1264**, the expansion memory **1274**, or memory on the processor **1252**. In some implementations, the computer program product can be received in a propagated signal, for example, over the transceiver **1268** or the external interface **1262**.

[0274] The mobile computing device **1250** can communicate wirelessly through the communication interface **1266**, which can include digital signal processing circuitry where necessary. The communication interface **1266** can provide for communications under various modes or protocols, such as GSM voice calls (Global System for Mobile communications), SMS (Short Message Service), EMS (Enhanced Messaging Service), or MMS messaging (Multimedia Messaging Service), CDMA (code division multiple access), TDMA (time division multiple access), PDC (Personal Digital Cellular), WCDMA (Wideband Code Division Multiple Access), CDMA2000, or GPRS (General Packet Radio Service), among others. Such communication can occur, for example, through the transceiver **1268** using a radio-frequency. In addition, short-range communication can occur, such as using a Bluetooth, WiFi, or other such transceiver (not shown). In addition, a GPS (Global Positioning System) receiver module **1270** can provide additional navigation- and location-related wireless data to the mobile computing device **1250**, which can be used as appropriate by applications running on the mobile computing device **1250**.

[0275] The mobile computing device **1250** can also communicate audibly using an audio codec **1260**, which can receive spoken information from a user and convert it to usable digital information. The audio codec **1260** can likewise generate audible sound for a user, such as through a speaker, e.g., in a handset of the mobile computing device **1250**. Such sound can include sound from voice telephone calls, can include recorded sound (e.g., voice messages, music files, etc.) and can also include sound generated by applications operating on the mobile computing device **1250**.

[0276] The mobile computing device **1250** can be implemented in a number of different forms, as shown in the figure. For example, it can be implemented as a cellular telephone **1280**. It can also be implemented as part of a smart-phone **1282**, personal digital assistant, or other similar mobile device.

[0277] Various implementations of the systems and techniques described here can be realized in digital electronic circuitry, integrated circuitry, specially designed ASICs (application specific integrated circuits), computer hardware, firmware, software, and/or combinations thereof. These various implementations can include implementation in one or more computer programs that are executable and/or interpretable on a programmable system including at least one programmable processor, which can be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device.

[0278] These computer programs (also known as programs, software, software applications or code) include machine instructions for a programmable processor, and can be implemented in a high-level procedural and/or object-oriented programming language, and/or in assembly/machine language. As used herein, the terms machine-readable medium and computer-readable medium refer to any computer program product, apparatus and/or device (e.g., magnetic discs, optical disks, memory, Programmable Logic Devices (PLDs)) used to provide machine instructions and/or data to a programmable processor, including a machine-readable medium that receives machine instructions as a machine-readable signal. The term machine-readable signal refers to any signal used to provide machine instructions and/or data to a programmable processor.

[0279] To provide for interaction with a user, the systems and techniques described here can be implemented on a computer having a display device (e.g., a CRT (cathode ray tube) or LCD (liquid crystal display) monitor) for displaying information to the user and a keyboard and a pointing device (e.g., a mouse or a trackball) by which the user can provide input to the computer. Other kinds of devices can be used to provide for interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback (e.g., visual feedback, auditory feedback, or tactile feedback); and input from the user can be received in any form, including acoustic, speech, or tactile input.

[0280] The systems and techniques described here can be implemented in a computing system that includes a back end component (e.g., as a data server), or that includes a middleware component (e.g., an application server), or that includes a front end component (e.g., a client computer having a graphical user interface or a Web browser through which a user can interact with an implementation of the systems and techniques described here), or any combination of such back end, middleware, or front end components. The components of the system can be interconnected by any form or medium of digital data communication (e.g., a communication network). Examples of communication networks include a local area network (LAN), a wide area network (WAN), and the Internet.

[0281] The computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

[0282] While this specification contains many specific implementation details, these should not be construed as limitations on the scope of the disclosed technology or of what may be claimed, but rather as descriptions of features that may be specific to particular embodiments of particular disclosed technologies. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment in part or in whole. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable subcombination. Moreover, although features may be described herein as acting in certain combinations and/or initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination. Similarly, while operations may be described in a particular order, this should not be understood as requiring that such operations be performed in the particular order or in sequential order, or that all operations be performed, to achieve desirable results. Particular embodiments of the subject matter have been described. Other embodiments are within the scope of the following claims.

Claims

1-20. (canceled)

21. A method for event detection and response, the method comprising: receiving sensor data associated with an environment; processing the sensor data using artificial intelligence (AI) to detect an event in the environment, wherein the AI is trained to correlate the received sensor data with different types of events; generating, based on the detected event, egress guidance for a user in the environment; returning instructions for presenting the egress guidance by a sensor device; and iteratively updating the egress guidance for the user based on (i) the sensor data and (ii) user feedback that is received from the sensor device.

22. The method of claim 21, wherein the AI is trained to: determine that at least one signal in the received sensor data exceeds a respective threshold condition beyond a threshold level; identify one or more other signals in the received sensor data that each exceeds respective threshold conditions beyond respective threshold levels at a similar time as the at least one signal; and correlate the identified one or more signals with the at least one signal to detect the event in the environment.

23. The method of claim 22, wherein the at least one signal is an increase in decibel readings in the environment where the event is detected.

24. The method of claim 22, wherein the one or more other signals comprise movements or motion proximate a location where the event is detected.

25. The method of claim 21, wherein the AI is trained to correlate the sensor data that is received from a plurality of different types of sensors with the different types of events.

26. The method of claim 21, wherein the AI is trained to correlate the sensor data that is received from different types of sensor in a network of sensor with the different types of events.

27. The method of claim 21, wherein the different types of events comprise safety events.

28. The method of claim 21, wherein the method further comprises returning the instructions for presenting the egress guidance to a mobile device of the user.

29. The method of claim 21, wherein returning the instructions for presenting the egress guidance further comprises presenting, by the sensor device, information for guiding an emergency response personnel to another user in the environment.

30. A system for egress guidance, the system comprising: a sensor device positioned in an environment and configured to generate sensor data associated with the environment; and a computer system in network communication with the sensor device, wherein the computer system is configured to perform a process comprising: receiving the sensor data from the sensor device; processing the sensor data using artificial intelligence (AI) to detect an event in the environment, wherein the AI was trained to correlate the received sensor data with different types of events; generating, based on the detected event, egress guidance for a user in the environment; and returning instructions for presenting the egress guidance by a computing device for the user.

31. The system of claim 30, wherein the process further comprises iteratively updating the egress guidance, using the AI, for the user based on (i) the sensor data and (ii) user feedback that is received from the sensor device.

32. The system of claim 30, wherein the computing device comprises a mobile device of the user.

33. The system of claim 30, wherein the computing device comprises the sensor device.

34. The system of claim 30, wherein the computer system comprises the sensor device.

35. The system of claim 30, wherein the computing device is configured to present the egress guidance with augmented reality (AR) projected on surfaces proximate the user.

36. The system of claim 30, wherein the computer system is remote from the environment.

37. The system of claim 30, wherein the user is an emergency response personnel and wherein returning the instructions for presenting the egress guidance comprises presenting, at the computing device for the user, information for guiding the emergency response personnel to another user in the environment.

38. A system for egress guidance, the system comprising: a sensor device positioned in an environment and configured to generate sensor data associated with the environment; and a computer system in network communication with the sensor device, wherein the computer system is configured to perform a process comprising: receiving the sensor data from the sensor device; processing the sensor data using artificial intelligence (AI) to detect an event in the environment; generating, based on the detected event, egress guidance for a user in the environment; returning instructions for presenting the egress guidance by a computing device for the user; and iteratively updating the egress guidance, using the AI, for the user based on (i) the sensor data and (ii) user feedback that is received from the sensor device.

39. The system of claim 38, wherein the computing device is configured to present the egress guidance with augmented reality (AR).

40. The system of claim 38, wherein the method further comprises returning the instructions for presenting the egress guidance to a mobile device of the user.